

Elcometer 266 DC Holiday Detector



Elcometer 266 DC Holiday Detector

The Elcometer 266 DC Holiday Detector provides accurate detection of pinholes, flaws, inclusions, thin spots and bubbles in a coating.

The gauge has been specifically designed to revolutionise high voltage DC testing of coatings, making it safer, easier and more reliable than previously possible.

At a glance:

Safer, easier & more reliable testing than ever before

Avoids coating damage by limiting current

Ideal for field, site or laboratory testing

- **Current limiting to avoid coating damage:**
When the Elcometer 266 detects a flaw, and sparks, the current flow reduces to a low level, minimising risk to both the user & the coating.
- **Automatic voltage calculator:**
No need for lookup tables, simply enter the coating thickness value and select the standard & the gauge will automatically set the voltage.
- **Safety hand grip:**
Ensures that high voltage can only be generated when the handle is being held.
- **Internal jeep tester:**
Removing the need for 2 gauges. The closed loop system with internal voltmeter guarantees the voltage output at all times.
- **Specialised handle design:**
Extended ribbing on the handle provides an effective barrier between the high voltage and the user.
- **Rugged and waterproof to IP65:**
Rugged, waterproof IP65 case is sealed against the elements.
- **Accurate sensitivity adjustment:**
Allows use on metallised or slightly damp coatings.
- **Rechargeable & replaceable battery packs:**
Battery packs can be charged inside or outside the gauge.
- **Interchangeable handles:**
0.5–5kV, 0.5–15kV or 0.5–30kV adjustable in 0.1kV steps.

Pinhole & Porosity Detection

Premature corrosion of a substrate is usually due to the failure of the coating. A major cause of failure is the presence of flaws in the finished coating. Collectively referred to as a coating's porosity the main types of flaw are described below:

Runs & Sags
The wet coating moves under gravity leaving a thin dry film.

Cissing
Occurs when a coating does not re-flow to cover the voids generated by air bubbles being released from the surface of the coating.

Cratering
Occurs when the substrate is wet or if the coating has poor flow characteristics, thus creating voids in the coating.

Pinholes
Caused either by air entrapment which is then released from the surface, or by the entrapment of particulates (dust, sand etc) which do not stay in place.

Over Coating
If too much coating is applied to a substrate, as the coating cures it can crack from internal stresses of the coating.

Under Coating
Areas not coated, or the coating flows away from the particular edges, corners or a substrate and welds. Furthermore over a rough surface profile, insufficient coating may leave the profile's peaks exposed.

Can be used in accordance with:	
ANSI/AWWA C 213	AS3894.1
ASTM D4787	ASTM G 6
ASTM D5162	ASTM G 62
BS1344-11	EN14430
JIS G3491	JIS G3492
ISO 2746	NACE RP0274
NACE RP 04901	NACE RP0188

Part Number	D266----1	D266----2	D266----3
Voltage	UK 230V	EUR 220V	US 110V
Compatible with 0.5 – 5kV handle	✓	✓	✓
Compatible with 0.5 – 15kV handle	✓	✓	✓
Compatible with 0.5 – 30kV handle	✓	✓	✓
Waterproof IP65 case	✓	✓	✓
High voltage output accuracy	±5% or ±50V below 1000 Volts		
Measured current flow accuracy	±5% of full scale		
Display resolution	100 Volts, 1µA		
Output current	0 – 100µA maximum		
Operating temperature	0°C to 50°C (32°F to 120°F)		
Power supply	Internal rechargeable lithium ion battery, fully charged within 4 hours		
Typical battery life (backlight off)	DC5: 40 hours	DC15: 20 hours	DC30: 10 hours
Typical battery life (backlight on)	DC5: 20 hours	DC15: 15 hours	DC30: 8 hours
Instrument case	High impact ABS		
Earth lead length	10m (394")		
Dimensions	520 x 370 x 125mm (20.5 x 14.5 x 5")		
Weight	Base unit (including battery pack) 1.2kg (2.7lb) Handle: 0.6kg (1.3lb)		
Packing list	<p>Elcometer 266 DC Holiday Detector, lithium battery, curly connection cable for high voltage handle, 10m (394") earth signal return lead with crocodile clip, battery charger and mains cable, band brush, shoulder strap, tough plastic carrying case, operating instructions.</p> <p><i>The Elcometer 266 DC Holiday Detector does not include the handle, select the part number for your required handle voltage from the part numbers listed below.</i></p>		

Accessories					
			Voltage Output Volts	Coating Thickness	
				mm	mils
	T26620033-1	Elcometer 266 DC5 Handle	500 – 5,000	1.25	50
	T26620033-2	Elcometer 266 DC15 Handle	500 – 15,000	3.75	150
	T26620033-3	Elcometer 266 DC30 Handle	500 – 30,000	7.50	300
	T26620081	Second Hand Grip			
	T26620082	Elcometer models 236 and 136 to Elcometer 266 Adapter			
	T26620083	Models 780, 785 and 790 to Elcometer 266 Adapter			
	T26620084	Models SP, APS, AP/S1, AP/S2, 10/20 & 14/20 to Elcometer 266 Adapter			
	T26619975	Band Brush Probe			

	T26619988-1	Probe Extension Piece	mm	inches
	T26619988-2	Probe Extension Piece	500	19.7
			1000	39

			Electrode Only	mm	inches
	T26620022-1	Right Angle Wire Brush Probe	T99926621	250	9.8
	T26620022-2	Right Angle Wire Brush Probe	T99926622	500	19.7
	T26620022-3	Right Angle Wire Brush Probe	T99926623	1000	39

	T99916996	Earth Signal Return Lead	metres	inches
			10	395

			Electrode Only	mm	inches
	T26620022-11	Right Angle Rubber Probe	T99926731	250	9.8
	T26620022-12	Right Angle Rubber Probe	T99926732	500	19.7
	T26620022-13	Right Angle Rubber Probe	T99926733	1000	39
	T26620022-14	Right Angle Rubber Probe	T99926734	1400	55

			Rolling Spring Only	Pipe Diameter	
				mm	inches
	T26620024-1	Rolling Spring Assembly	T9996197A	50	2
	T26620024-2	Rolling Spring Assembly	T9996197B	75	3
	T26620024-3	Rolling Spring Assembly	T9996197C	100	4
	T26620024-4	Rolling Spring Assembly	T9996197D	150	6
	T26620024-5	Rolling Spring Assembly	T9996197E	200	8
	T26620024-6	Rolling Spring Assembly	T9996197F	250	10
	T26620024-7	Rolling Spring Assembly	T9996197G	300	12
	T26620024-8	Rolling Spring Assembly	T9996197H	350	14
	T26620024-9	Rolling Spring Assembly	T9996197I	400	16
	T26620024-10	Rolling Spring Assembly	T9996197J	450	18
	T26620024-11	Rolling Spring Assembly	T9996197K	500	20
	T26620024-12	Rolling Spring Assembly	T9996197L	600	24
T26620024-13	Rolling Spring Assembly	T9996197M	750	30	
T26620024-14	Rolling Spring Assembly	T9996197N	1000	36	

			Electrode Only	Pipe Diameter	
				mm	Inches
	T26620071-1	Circular Brush Probe Assembly	T9993766-	38	1.5
	T26620071-2	Circular Brush Probe Assembly	T9993767-	51	2
	T26620071-3	Circular Brush Probe Assembly	T9993768-	64	2.5
	T26620071-4	Circular Brush Probe Assembly	T9993769-	76	3
	T26620071-5	Circular Brush Probe Assembly	T9993770-	89	3.5
	T26620071-6	Circular Brush Probe Assembly	T9993771-	102	4
	T26620071-7	Circular Brush Probe Assembly	T9993772-	114	4.5
	T26620071-8	Circular Brush Probe Assembly	T9993773-	127	5
	T26620071-9	Circular Brush Probe Assembly	T9993774-	152	6
	T26620071-10	Circular Brush Probe Assembly	T9993775-	203	8
T26620071-11	Circular Brush Probe Assembly	T9993776-	254	10	
T26620071-12	Circular Brush Probe Assembly	T9993777-	305	12	

Additional Accessories				
	T26619950	Rechargeable Battery Pack		
	T26619893	Curly Connecting Cable		
	T26620085	Elcometer 266 Pipe Testing Kit		

Related Products



Elcometer 270

Elcometer 270 Pinhole Detector utilises the wet sponge technique and has been designed to set a new standard for wet sponge detectors – a high quality, low voltage detector with similar accessories to a high voltage spark tester.




Elcometer 260

The Elcometer 260 provides a quick, low cost method of testing coatings for pinholes. A UV fluorescing additive is applied to a base coat. When the UV flashlight shines on the coating, any areas where the base coat is not covered by subsequent coating, fluoresces and clearly identifies any pinholes.



Elcometer 236

The Elcometer 236 DC Holiday Detector is available in two versions: 0.5 – 15kV and 0.5 – 30kV. Each unit provides the user with complete control of voltage sensitivity settings. Due to the method of operation, the Elcometer 236 minimises the risk of additional coating damage and avoids the danger of coating popping off the surface which can occur with some high voltage systems.



Elcometer Catalogue

Elcometer has a wide range of products available across the complete coating process – from coatings development through to final inspection.

For further information contact Elcometer or visit www.elcometer.com to order a complete product catalogue.

ENGLAND

Elcometer Instruments Ltd
Edge Lane
Manchester M43 6BU

Tel: +44 (0)161 371 6000
Fax: +44 (0)161 371 6010
e-mail: sales@elcometer.com
www.elcometer.com

USA

Elcometer Inc
1893 Rochester Industrial Drive
Rochester Hills Michigan 48309

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com
www.elcometer.com

CANADA

Elcometer Ltd
PO Box 622, 401 Ouelette Avenue
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: ca_info@elcometer.com
www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd
896 Dunearn Rd
Sime Darby Centre #3-09
Singapore 589472,
Republic of Singapore

Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com
www.elcometer.com

BELGIUM

Elcometer SA
Rue Vallée 13
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.be
www.elcometer.be

FRANCE

Elcometer SARL
97 Route de Chécý
45430 BOU

Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.fr
www.elcometer.fr

GERMANY

Elcometer Instruments GmbH
Himmlingstraße 18
D-73434 Aalen

Tel: +49 (0)7366 91 92 83
Fax: +49 (0)7366 91 92 86
e-mail: de_info@elcometer.de
www.elcometer.de