



AUDIT 106 TECHNICAL DATA

| | | |
|--------------------------|---|-------------------|
| Display | 4 digit L.C.D | |
| Range | 1.5 mm to 99.9 mm or 0.060" to 3.999" | |
| Resolution | 0.1 mm or 0.004" | |
| Calibration | Preset selectable programmes | |
| | 0 Steel | 5 SG Iron |
| | 1 Stainless Steel | 6 Flake Iron |
| | 2 Aluminium | 7 Perspex / Nylon |
| | 3 Copper | 8 PVC |
| | 4 70 / 30 Brass | 9 Polypropylene |
| Power | 2 x AA alkaline cells, internally fitted | |
| Battery Life | Approx 100 hours continuous use, equivalent to many weeks in practical situations | |
| Low Battery | Warning displayed when approx. 10 hours of continuous use remain. | |
| Auto Off | Power automatically switched off 60 seconds after last use. | |
| Display Hold | 5 seconds from probe lift-off. | |
| Environmental Protection | Sealed to IP65 | |
| Temperature Range | Operation: -5 to +55° C Storage: -20 to +70° C | |
| Weight | 290g | |
| Dimensions | 151 x 82 x 33 mm | |

STANDARD EQUIPMENT

Each **AUDIT 106** is supplied with:

DT25, 5MHz probe fitted with integral lead

Ultrasonic coupling agent in 125 ml container

2 x AA alkaline cells

Moulded plastic transit case

Operator manual

[Home](#)

