

EUROPE'S LARGEST SELECTION OF TEST & MEASUREMENT EQUIPMENT FOR HIRE

INLEC.COM

DATA-SHEET



Nationwide Low Call
0333 6000 600

WHY BUY
WHEN YOU CAN HIRE

Fluke 1630

Earth Ground Clamp Meter

Technical Data

Earth Ground loop resistance measurements for commercial, industrial, and utility applications

The clamp-on ground testing technique used by the Fluke 1630 simplifies ground loop testing and enables non-intrusive leakage current measurement.

The compact and rugged design makes the Fluke 1630 easy to use in small places and harsh environments, while the “Display-Hold” and the continuity testing with an audible alarm function, ensures convenience in use. The novel technique means that earth ground loop testing and continuity testing can be completed without breaking the circuit.



- A wide ground loop resistance range, from 0.025 Ω to 1500 Ω, to satisfy all requirements
- Large jaw opening of 35 mm (1.38 in) for tests on ground conductors and/or equipotential bus bars
- Measurement of ground leakage current, from 0.2 mA to 1000 mA, without needing to disconnect - ideal for system troubleshooting
- Wide ac current measurement range from 0.2 A to 30 A allows one instrument for multiple applications
- Continuity loop test - quickly assess whether resistance is less than 40 Ω, with audible alarm
- User-defined HI / LO Alarm limits, for rapid measurement evaluation
- Handy “Display-Hold” button for capturing readings in hard-to-reach places
- Time saving memory function automatically records and stores measured values
- Automatic self calibration ensures correct measurement every time

Stakeless testing system

The Fluke 1630 uses the Stakeless testing method, which eliminates the need to disconnect parallel ground rods and find suitable locations for placing auxiliary ground stakes. This saves time and enables users such as industrial and utility electricians, and field service electricians and contractors, to perform earth ground loop tests in locations where it is not possible to use other techniques, such as inside buildings or on power pylons. With the Stakeless testing method, earth ground stakes are no longer necessary. The Fluke 1630 Earth Ground Clamp is placed around the earth ground rod or the connecting cable. A known voltage is induced by one half of the clamp and the current is measured by the other half. The tester automatically determines the ground loop resistance at this grounding connection.

Applications

- Earth Ground loop testing in various installations - for example, high voltage pylons, buildings, cell phone substations, RF transmitters, etc.
- Inspection of lightning protection systems
- Leakage current measurement

General specifications

Operating error	Refers to the operating temperature range and is guaranteed for 2 years
Storage temp. range	-20 °C to 60 °C (-4 °F to 140 °F)
Reference temp. range	23 °C ± 5 °C (73 °F ± 9 °F)
Storage humidity	< 75 % R _H
Operating humidity	< 85 % R _H
Display	9999 digit LC-display with special symbols
Protection	IP20 according to IEC 529/EN 60529
Safety	300 V, CAT III / pollution degree 2 IEC 61010-1
Weight	640 g (1.4 lb)
Conductor size	35 mm (1.38 in) approximately
Dimension (length x width x depth)	257 mm x 100 mm x 47 mm (1 in x 3.9 in x 1.9 in)
Emission	IEC 1000 4-2, IEC 61326-1 class B
Immunity	IEC 61000-4-2, 8 kV (air) criteria A IEC 61000-4-3, 3 V/m performance criteria A
Range selection	Auto
Overload indicator	"OL" on display
Measuring time	0.4 sec
Measuring frequency	3.333 kHz
Battery type	9 V alkaline (type IEC 6 LR 61)
Battery life	≥ 8 hours (continuous operation)
Power consumption	40 mA
Low battery indication	Display symbol

Ground Loop Resistance (Autorange)

Operating temperature: 0 °C to 50 °C (14 °F to 122 °F)

Range	Resolution	Operating error ¹
0.025 - 0.250 Ω	0.002 Ω	± 1.5 % rdg ± 0.05 Ω
0.250 - 9.999 Ω	0.02 Ω	± 1.5 % rdg ± 0.1 Ω
10.00 - 99.99 Ω	0.04 Ω	± 2.0 % rdg ± 0.3 Ω
100.0 - 199.9 Ω	0.4 Ω	± 3.0 % rdg ± 1.0 Ω
200.0 - 400.0 Ω	2 Ω	± 5.0 % rdg ± 5 Ω
400.0 - 600.0 Ω	5 Ω	± 10 % rdg ± 10 Ω
600.0 - 1500 Ω	20 Ω	± 20 %

¹Note: Loop resistance with no inductance, external magnetic field < 50 A/m, external electrical field < 1 V/m, conductor centered.

Continuity

Beep if resistance < approx. 40 Ω

Ground/leakage current mA~

(Autorange, 50/60 Hz, true-rms, crest factor < 3.0)

Operating temperature: -10 °C to 50 °C (14 °F to 122 °F)

Range	Resolution	Operating error
0.200 - 1.000 mA	0.001 mA	± 2.5 % rdg ± 0.05 mA
1.00 - 10.00 mA	0.01 mA	± 2.5 % rdg ± 0.05 mA
10.0 - 100.0 mA	0.1 mA	± 2.0 % rdg ± 0.3 mA
100 - 1000 mA	1 mA	± 2.0 % rdg ± 3 mA

Current A~

(Autorange, 50/60 Hz, true-rms, crest factor < 3.0)

Operating temperature: -10 °C to 50 °C (14 °F to 122 °F)

Range	Resolution	Operating error
0.20 - 15.00 A	0.01 A	± 2.0 % rdg ± 0.03 A
15.00 - 30.00 A	0.01 A	± 3.0 % rdg ± 0.03 A

HI/LO Limit Evaluation

Values from 0 Ω to 1510 Ω may be preset for automatic comparison. If the measured value is outside of the limit an audible and visual signal is given.

Recording

Measured values can be saved or logged with a defined time interval from 1 to 255 s. Recorded values may then be recalled on the display of the instrument.

The Fluke 1630 Earth Ground Clamp Meter includes:

- Carrying case with strap
- Resistance test loop
- Users manual in English, French, Spanish, German, Italian, Portuguese and Simplified Chinese



Fluke. Keeping your world up and running.™

Fluke Corporation
PO Box 9090, Everett, WA USA 98206

Fluke Europe B.V.
PO Box 1186, 5602 BD
Eindhoven, The Netherlands

For more information call:
In the U.S.A. (800) 443-5853 or
Fax (425) 446-5116
In Europe/M-East/Africa +31 (0) 40 2675 200 or
Fax +31 (0) 40 2675 222
In Canada (800)-36-FLUKE or
Fax (905) 890-6866
From other countries +1 (425) 446-5500 or
Fax +1 (425) 446-5116
Web access: <http://www.fluke.com>

©2006 Fluke Corporation. All rights reserved.
Specifications subject to change without notice.
Printed in U.S.A. 12/2006 Pub_ID: 11200-eng

INLEC, supporting you to deliver a world class service, every day, in every sector ...



OUR COMMITMENT TO YOU

A wealth of knowledge and experience.

You can take advantage of expert advice to ensure you get the best, most appropriate and cost effective equipment for the job. We supply a wide variety of industries, so if there is another way to do the job or save you time and money we'll pass on the benefit of our experience for free.

Honest advice, just a phone call away.

If we don't have a particular item, rather than hiring you something that won't do the job, we would rather direct you to an alternative supplier. You will always be provided with full instructions and if you still need help, call our technical team on Nationwide Low Call 0333 6000 600. Our aim is to save you time, frustration and money.

Top quality equipment from major manufacturers.

With Inlec you'll get the most accurate, reliable and well-maintained equipment available. Prices are regularly reviewed to ensure you always enjoy the best value for money. We have made a significant investment in test equipment so we ensure that it's well packed to minimise damage and delay.

We really do listen to you.

You won't waste your time contacting Inlec. Every request for equipment is logged and carefully considered. Listening to our customers helps keep our product range up to date and relevant. If you are unhappy about any aspect of our service please let us know so we can put it right.

YOUR 5 WAY GUARANTEE

1 GUARANTEE SAME DAY DESPATCH

We understand why prompt delivery is important to you. So, if we confirm your order before 3pm, you are guaranteed same day despatch.

2 OUR PRICE GUARANTEE

Inlec guarantee you real value for money. Our price match policy is simple - if you can hire the same product for less elsewhere, we guarantee to match that price and reduce it by a further 10% of the difference - and still deliver our industry leading technical and customer support.

For full details check our price-match guarantee online

3 TOP QUALITY GUARANTEED

All equipment is thoroughly checked prior to dispatch to ensure you receive it in full, safe working order. Your shipment will be securely packed and include manufacturer's instructions, accessories or consumables and a valid calibration certificate where appropriate. In addition, Inlec offer a 24 hour replacement service if you decide the equipment is not suitable for your application*.

4 FRIENDLY, KNOWLEDGEABLE ADVICE GUARANTEED

Inlec are happy to provide you with free advice, from an unbeatable team of experienced, knowledgeable and friendly engineers and hire experts.

5 YOUR GUARANTEE OF THE BEST CUSTOMER SERVICE

Throughout your hire we will work hard to ensure you enjoy the very best in support and service from Inlec. We guarantee you won't find better service anywhere in the industry.

*subject to availability and conditions

Europe's leading Test Equipment Hire Specialist



LAB NO. 0535



Nationwide Low Call 0333 6000 600

Online: www.inlec.com

Inlec UK Ellerbeck Way, Stokesley Business Park, Stokesley N Yorkshire TS9 5JZ United Kingdom



CERT. NO. GB93/1773



Accredited Contractor