INLEC.COM



Nationwide Low Call 0333 6000 600



705/707/715/787 Loop Calibrators



4-20 mA, source, measure, simulate



200000





705 Loop Calibrator

- Simultaneous mA and %
- mA accuracy of 0.02
- Measure, source and simulate mA
- Push button 25% steps for fast, easy linearity checks.
- "Span Check" for fast confirmation of zero and span.
- Selectable slow ramp, fast ramp, and step function .
- 24 volt internal loop supply.
- 0 20 mA or 4 20 mA default start up modes.

707 Loop Calibrator

- Features of the Fluke 705
- "Quick Click" detented rotary knob for one handed operation
- Higher accuracy: 0.015%
- Mains Voltage Input protection

Specifications

 250 Ohm loop resistance for with Hart instrumentation



715 Volt/mA Calibrator

- Measure loop current (0-20 mA, 4-20 mA) signals with 0.015% accuracy and 0.001 mA resolution
- Measure voltage output process signals from PLCs, transmitters
- Source or simulate 24 mA loop current
- Source voltage to 100 mV or 10V
- 24V loop supply with simultaneous current measurement

787 ProcessMeter

- DMM and loop calibrator in one tool
- Precision 1000V, 440 mA digital multimeter
- DC current source/loop calibrator
- Clear LCD with backlight; 4000 counts (30 000 counts for DC current)
- Externally accessible battery for easy battery changes
- 1000V overload protection on V, ohms, frequency
- Meets 1000 volt EN61010-1 CAT III standards
- Min/Max/Average/Hold/Relative modes

Functions

EN 61010-1

Functions	705/707	715	787	
Voltage measurement				
Range	0-28 V DC	0-100 mV, 0-10 V	0-1000 V AC or DC	
Resolution	1 mV	10 μV 1 mV	0.1 mV to 1.0 V	
Accuracy	0.025% Rdg + 1 LSD(705) 0.015% Rdg + 2 LSD(707)	0.02% Rdg + 2 LSD	0.1% Rgd + 1 LSD (VDC)	
Current measurement				
Range	0-24 mA	0-24 mA	0-1 A	0-30 mA
Resolution	0.001 mA	0.001 mA	1 mA	0.001 mA
Accuracy	0.015% + 2 LSD (707)	0.015%	0.2%+2 LSD	0.05%+2 LSD
Current sourcing				
Range	0-20 mA or 4-20 mA1	0-20 mA or 4-20 mA1	0-20 mA or 4-20 mA1	
Accuracy	0.015% Rdg + 2 LSD (707)	0.015% + 2 LSD	0.05% of span	
Drive capability	1000 Ω @ 24 mA	1000 Ω @ 24 mA	500 Ω @ 24 mA	
Loop power while measuring mA	24 V	24 V	N/A	
Voltage sourcing	N/A	0-100 mV or 0-10 V	N/A	
Resistance measurement	N/A	N/A	to 40 MΩ, 0.2% + 1 LSD	
Frequency	N/A	N/A	to 19.999 kHz, 0.005% + 1 LSD	
Diode test	N/A	N/A	2.4 V shows diode voltage drop	
Continuity	N/A	N/A	Beeps for resistance <100 ohms	
Display current and % of span	Yes	mA or %	Yes	
Auto step, auto ramp	Yes	No	Yes	
Span Check	Yes	No	No	
Battery life	18 hours typical, at 12 mA	4-20 hours, typical, depending on functions used	50 hours typical, 12 hours sourcing 12 mA	

will over-range to 24 mA

Accessories and Ordering Information

Included Accessories
Fluke 705/707: C10 Protective Yellow Holster,
TL75 Test Leads, AC70 Test Clips,
Instruction Sheet (14 languages).
Fluke 715: C81Y Protective Yellow Holster
with Flex-Stand, Test Leads and Alligator
Clips, Single 9V alkaline battery,
Instruction Sheet (14 languages).
Fluke 787: C81Y Protective Yellow Holster
with Flex-Stand, TL75 Safety-Designed
Test Lead Set plus AC70A Alligator Clips,
one 9V alkaline battery, Users Manual.

Ordering Information



INLEC, supporting you to deliver a world class service, every day, in every sector ...













OUR COMMITMENT TO YOU

A wealth of knowledge and experience.

You can take advantage of expert advice to ensure you get the best, most appropriate and cost effective equipment for the job. We supply a wide variety of industries, so if there is another way to do the job or save you time and money we'll pass on the benefit of our experience for free.

Honest advice, just a phone call away.

If we don't have a particular item, rather than hiring you something that won't do the job, we would rather direct you to an alternative supplier. You will always be provided with full instructions and if you still need help, call our technical team on Nationwide Low Call 0333 6000 600. Our aim is to save you time, frustration and money.

Top quality equipment from major manufacturers.

With Inlec you'll get the most accurate, reliable and well-maintained equipment available. Prices are regularly reviewed to ensure you always enjoy the best value for money. We have made a significant investment in test equipment so we ensure that it's well packed to minimise damage and delay.

We really do listen to you.

You won't waste your time contacting Inlec. Every request for equipment is logged and carefully considered. Listening to our customers helps keep our product range up to date and relevant. If you are unhappy about any aspect of our service please let us know so we can put it right.

YOUR 5 WAY GUARANTEE

1 GUARANTEE SAME DAY DESPATCH

We understand why prompt delivery is important to you. So, if we confirm your order before 3pm, you are guaranteed same day despatch.

OUR PRICE GUARANTEE

Inlec guarantee you real value for money. Our price match policy is simple - if you can hire the same product for less elsewhere, we guarantee to match that price and reduce it by a further 10% of the difference - and still deliver our industry leading technical and customer support.

For full details check our price-match quarantee online

3 TOP QUALITY GUARANTEED

All equipment is thoroughly checked prior to dispatch to ensure you receive it in full, safe working order. Your shipment will be securely packed and include manufacturer's instructions, accessories or consumables and a valid calibration certificate where appropriate. In addition, Inlec offer a 24 hour replacement service if you decide the equipment is not suitable for your application*.

FRIENDLY, KNOWLEDGEABLE ADVICE GUARANTEED

Inlec are happy to provide you with free advice, from anunbeatable team of experienced, knowledgeable and friendly engineers and hire experts.

9 YOUR GUARANTEE OF THE BEST CUSTOMER SERVICE

Throughout your hire we will work hard to ensure you enjoy the very best in support and service from Inlec. We guarantee you won't find better service anywhere in the industry.

*subject to availability and conditions

Europe's leading Test Equipment Hire Specialist









