

EUROPE'S LARGEST SELECTION OF TEST & MEASUREMENT EQUIPMENT FOR HIRE

**INLEC.COM**

# DATA-SHEET



Nationwide Low Call  
**0333 6000 600**

**WHY BUY**  
WHEN YOU CAN HIRE

# OTS80PB and OTS60PB

## Portable oil test sets



- **Light-weight, rugged, portable instruments for measuring insulating oil breakdown voltage**
- **Lock in precision - oil vessel with lockable adjustment**
- **Bright 3.5 inch colour display visible out doors**
- **Suitable for mineral, ester and silicon oils**
- **Trip detection circuit with direct measurement of voltage and current**
- **Ultra fast (<10  $\mu$ s) HV switch off time**

### DESCRIPTION

Megger's automatic portable oil test sets perform accurate breakdown voltage tests on mineral, ester and silicon insulating liquids. Moulded test vessels give repeatable results in the field and laboratory with lock in precision electrode gap setting adjustment wheels. The transparent, shielded lid is a key feature enabling users to see what is happening within the test chamber.

Megger portable 60 kV and 80 kV oil test sets are the lightest on the market ranging from 16 kg to 23.5 kg depending on model and configuration. They come complete with optional carry bag and transport case. The carry bag has pouches for electrode accessory pack, leads, quick user guide, paper roll etc.

The units are mains powered with optional lead acid or NiMH batteries. In addition, an internal 12 V DC charger and vehicle adaptor cable is standard with either battery option.

Test standards are preloaded in the instrument and new versions can be uploaded via USB flash drive. Both portable instruments support the creation of user defined custom tests. Test results are identified either by a serial number or asset ID and are time and date stamped.

An optional internal printer provides a hard copy of results. Ink based printout ensures durability at all temperatures. USB interfaces (x3) support PC connection, USB flash drive and external USB printer.

User safety is paramount and Megger have designed independent and dual redundant high voltage cut-off circuitry to ensure safety. During a test the operator can terminate by pressing any button on the keyboard which will remove high voltage immediately and abort the test. The transparent lid provides ample visibility within the chamber yet is protected and electrically shielded by a screen with

multiple links to instrument ground.

### FEATURES AND BENEFITS

- Test voltages up to 60 kV or 80 kV
- Lock in precision oil vessel - lockable gap setting
- Flat electrode gap gauges that will not damage electrodes
- Automatic oil temperature measurement
- QVGA colour display with backlight
- Easy clean chamber with oil drain
- Safe operation with dual redundant micro-switch HV cut off, zero volt touch bar and screened lid
- Transparent lid results in highly visible test chamber and vessel
- Intuitive user interface supports fully automatic operation with preloaded international test standards plus user configurable test sequences

### OPTIONAL ITEMS

- Factory fitted lead-acid (OTS80PB only) or NiMH battery with 12 V charger and vehicle lead
- Internal printer
- Motorised lid impeller
- Voltage check unit (VCM100D/VCM80D)
- Carry bag
- Transport case

### APPLICATION

Monitoring and maintenance of oil quality is essential in ensuring the reliable operation of oil filled electrical equipment. Codes of practice have been established in many countries that include several different types of test on insulating oils.

One of the fundamental tests of oil quality is the breakdown voltage test, which is a measure of the oil's ability to withstand electric stress. A low breakdown voltage can indicate the presence of contaminants such as water or conducting particles.

Care should be taken to ensure the process of sampling oil and subsequent testing does not in any way contaminate it with foreign objects. Cleaning vessels between oil tests should be a rinse with the next sample, never clean with fibrous materials. To ensure an accurate reading set gap carefully and lock adjusting wheels.

## SPECIFICATIONS

### Test voltage

**OTS 60PB** -30 to +30 kVrms

**OTS 80PB** -40 to +40 kVrms

**Voltage resolution** 0.1 kV,  $\pm 1\%$ ,  $\pm 2$  digits

### Programmed test sequences

ASTM D 1816-04	BS EN 60156-96	SABS EN60156
ASTM D 877A-02	CEI EN 60156-95	VDE0370 part 5
ASTM D 877B-02	IRAM 2341	AS1767.2.1
IEC 60156-95	UNE EN 60156	PA SEV EN60156
	NF EN 60156	JIS C 2101-99 (M)
		JIS C 2101-99 (S)
		plus 3 custom test sequences

### Vessels 400 ml (standard) 150 ml (option)

Nylon 12 chamber provides precision electrode alignment and adjustment wheels lock electrodes in position, option of 150 ml vessel for low volume oil samples

### Oil temperature measuring range

10 °C to 65 °C

### Oil temperature sensor resolution

1 °C

### Power supply

Line voltage 85 to 265 VAC  
Line frequency 50/60 Hz

### Batteries (option)

Lead acid 2 x 12 V 4 Ah,  
or NiMH 24 V 2 Ah

### Interfaces

USB 2.0 compatible  
2 x USB type-A (memory stick)  
1 x USB type-B (printer or PC)

### Internal printer (option)

Matrix impact printer  
Paper 57.5 mm wide

### External printer

Any printer with USB interface and PCL3 driver

### Protection

Safety interlock on cover

### Display

320 x 240 QVGA colour display with backlight

### Dimensions

**OTS 60PB** 520 mm x 340 mm x 250 mm

**OTS 80PB** 520 mm x 380 mm x 250 mm

### Weight

#### OTS 60PB

16 kg (printer, no battery),  
16.8 kg (printer, NiMH battery)

#### OTS 80PB

20 kg (printer, no battery),  
20.8 kg (printer, NiMH battery),  
23.2 kg (printer, lead acid batteries)

### Test vessels

1.1 kg (400 ml and 150 ml)

### Environmental

#### Operating temperature

0 °C to +50 °C

#### Storage temperature

-30 °C to +65 °C

#### Humidity

80% RH at 40 °C operation  
95% RH at 40 °C storage

### Safety

Designed in accordance with IEC61010

### EMC

Light industrial IEC 61326-1 Class B, CISPR 22, CISPR 16-1 and CISPR 16-2

### Langauges

English, French, German, Spanish, Chinese, Czech, Dutch, Finnish, Italian, Norwegian, Polish, Portuguese, Russian and Swedish.



VCM100D/CM80D



400 ml vessel assembly (electrodes fitted)
















**Programmed test sequence overview**

Standards complied with and programmed	Oil types tested		Electrode gap options (mm)				Electrode shape options			Oil stirring options			Voltage rise rate options			Breakdown test sequence		
	Mineral Ester HMWH	Silicon	1.0	2.0	2.5	2.54							0.5 kV/s	2 kV/s	3 kV/s	Number of tests	Initial stand time	Time between tests
IEC 60156-95	■	■		■			■			■			■			6	5 mins	2 mins
BS EN 60156-96	■	■		■			■			■			■			6	5 mins	2 mins
CEI EN 60156-95	■	■		■			■			■			■			6	5 mins	2 mins
IRAM 2341	■	■		■			■			■			■			6	5 mins	2 mins
UNI EN 60156	■	■		■			■			■			■			6	5 mins	2 mins
NF EN 60156	■	■		■			■			■			■			6	5 mins	2 mins
SABS EN 60156	■	■		■			■			■			■			6	5 mins	2 mins
VDE 0370 part 5	■	■		■			■			■			■			6	5 mins	2 mins
AS1767.2.1	■	■		■			■			■			■			6	5 mins	2 mins
PA SEV EN 60156	■	■		■			■			■			■			6	5 mins	2 mins
JIS C 2101-99 (M)	■			■			■			■				■		5 x 2	2 mins	1 min
JIS C 2101-99 (S)		■		■			■			■				■		1 x 5	2 mins (x5)	N/A
ASTM D 1816-04	■	■	■					■			■		■			5	3 mins	1 min 15s
ASTM D 877A-02	■	■				■			■							5	2 mins	1 min
ASTM D 877B-02	■	■				■			■							1 x 5	2 mins (x5)	N/A
Custom tests (x3) (Programmable)	■	■	1.0 to 7.0				■			■			0.5 kV/s to 5 kV/s			5, 6 or 10	10s to 600s	10s to 600s

## ORDERING CONFIGURATION

Example of an ordering configuration:-

OTS80PB-EU2-EP-4C = This order is for an OTS80PB with EU power lead, NiMH battery, IEC electrode set, internal printer, lid stirrer and carry bag.

Model:		OTS	PB-	-	-	-	-	-	Weights
Select model	80 kV	80							19.4 kg
	60 kV	60							15.3 kg
Select power cord		EU lead	EU						
		UK lead	UK						
		US lead	US						
		Australian lead	AU						
		No Plug lead	BL						
Select battery option		Sealed lead acid	1	OTS80PB ONLY					3.3 kg
		NiMH	2						0.8 kg
	NONE	No battery	X						0 kg
Select electrode set		ASTM set	A						
		IEC set	E						
		Full set	U						
Select printer option		Internal printer	P						0.54 kg
		No printer	X						0.08 kg
Select stirrer option		Stirrer lid assembly fitted	4						0.3 kg
		Stirrer lid assembly not fitted	X						
Select carry case option		Carry case	C						1.3 kg
		No carry case	X						



# INLEC, supporting you to deliver a world class service, every day, in every sector ...



## OUR COMMITMENT TO YOU

### A wealth of knowledge and experience.

You can take advantage of expert advice to ensure you get the best, most appropriate and cost effective equipment for the job. We supply a wide variety of industries, so if there is another way to do the job or save you time and money we'll pass on the benefit of our experience for free.

### Honest advice, just a phone call away.

If we don't have a particular item, rather than hiring you something that won't do the job, we would rather direct you to an alternative supplier. You will always be provided with full instructions and if you still need help, call our technical team on Nationwide Low Call 0333 6000 600. Our aim is to save you time, frustration and money.

### Top quality equipment from major manufacturers.

With Inlec you'll get the most accurate, reliable and well-maintained equipment available. Prices are regularly reviewed to ensure you always enjoy the best value for money. We have made a significant investment in test equipment so we ensure that it's well packed to minimise damage and delay.

### We really do listen to you.

You won't waste your time contacting Inlec. Every request for equipment is logged and carefully considered. Listening to our customers helps keep our product range up to date and relevant. If you are unhappy about any aspect of our service please let us know so we can put it right.

## YOUR 5 WAY GUARANTEE

### 1 GUARANTEE SAME DAY DESPATCH

We understand why prompt delivery is important to you. So, if we confirm your order before 3pm, you are guaranteed same day despatch.

### 2 OUR PRICE GUARANTEE

Inlec guarantee you real value for money. Our price match policy is simple - if you can hire the same product for less elsewhere, we guarantee to match that price and reduce it by a further 10% of the difference - and still deliver our industry leading technical and customer support.

For full details check our price-match guarantee online

### 3 TOP QUALITY GUARANTEED

All equipment is thoroughly checked prior to dispatch to ensure you receive it in full, safe working order. Your shipment will be securely packed and include manufacturer's instructions, accessories or consumables and a valid calibration certificate where appropriate. In addition, Inlec offer a 24 hour replacement service if you decide the equipment is not suitable for your application\*.

### 4 FRIENDLY, KNOWLEDGEABLE ADVICE GUARANTEED

Inlec are happy to provide you with free advice, from an unbeatable team of experienced, knowledgeable and friendly engineers and hire experts.

### 5 YOUR GUARANTEE OF THE BEST CUSTOMER SERVICE

Throughout your hire we will work hard to ensure you enjoy the very best in support and service from Inlec. We guarantee you won't find better service anywhere in the industry.

\*subject to availability and conditions

## Europe's leading Test Equipment Hire Specialist



LAB NO. 0535



Nationwide Low Call 0333 6000 600

Online: [www.inlec.com](http://www.inlec.com)

Inlec UK Ellerbeck Way, Stokesley Business Park, Stokesley N Yorkshire TS9 5JZ United Kingdom



CERT. NO. GB93/1773

