EUROPE'S LARGEST SELECTION OF TEST & MEASUREMENT EQUIPMENT FOR HIRE

INLEC.COM

WHEN YOU CAN HIRE

Nationwide Low Call 0333 6000 600

Megger.

TDR2000/3 Advanced Dual Channel TDR



- Comprehensive Dual Channel capability with dual aspect display.
- AUTO set up mode for instant use.
- Ultra fast pulse for near end fault identification.
- Xpert guidance to potential fault.
- IP54 rating offers real life working.
- Designed for use on all metallic paired cables.

DESCRIPTION

The Megger® TDR2000/3 is a state of the art, dual channel, high resolution, colour screen, compact Time Domain Reflectometer for locating faults on paired metallic cables.

The TDR2000/3 has a minimum resolution of 0.1m/0.3ft and a 20km/60kft maximum range depending on the velocity factor selected and the cable type.

Five output impedances are available (25, 50, 75, 100 and 125 ohms) and with an auto impedance matching feature and a velocity factor between 0.2 and 0.99 to meet any cable test requirements

FEATURES AND BENEFITS

The TDR2000 has a large, high resolution, colour, WVGA display with easy set up features. Directional control buttons, together with soft keys, provide intuitive and easy operation for the user.

An AUTO selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the TDR trace. The ability to manually override the auto function allows fine tuning to enable identification of hard to determine faults.

Dual trace and dual cursor capabilities allow full flexibility, giving the operator full control and instant indication of distance between two points.

A trace comparison feature also allows close examination between trace conditions. Extra high resolution together with white-light backlight, user definable tones and colour give the graphical display a vibrance aiding the user in identifying key events on the trace.

Trace Storage

100 internal trace memories provide for the storage and recall of test results. The traces can be recalled to the display for analysis or compared with an active display to aid in fault location.

Alternatively the stored results can be downloaded to a computer, over the USB port, using the TraceXpert software and USB lead provided.

Fault identification

Megger's own built-in Xpert mode allows for speedy identification of faults. One press of the Xpert key automatically adjusts the range and gain and positions the cursor to the first major event on the cable. Press the Xpert key again and the TDR2000/3 will jump to the next detected disturbance.

For those who wish to maintain manual control, manual mode allows full override access to refine the response for easy fault identification.

TraceXpert PC software

The TDR2000/3 comes complete with the Megger TraceXpert software which gives full control over results downloading, reporting and uploading of saved traces. Designed around a database and programmed for ease of use and simplicity, TraceXpert offers the ideal application for all your data processing requirements.

Megger.

MODELS

The TDR2000/3 is available in two models.

- TDR2000/3 A fully featured high resolution TDR with backlit colour display and powered by Li-ion rechargeable battery batteries. This model comes complete with 2 pairs of mini-clip Test Leads.
- TDR2000/3P The same as the TDR2000/3 but with Dual fused test leads replacing the mini-clip leads

BENEFITS

- Backlit graphics colour LCD (800x480)
- Adjustable display contrast
- Resolution to 0.1 m
- Trace Xpert guide to potential fault location
- 100 trace on board memory
- USB connection to PC allowing upload and download of traces
- "TraceXpert" PC software analysis tool
- For use on Telecom TNV-3 circuit, or 150V CAT IV power circuits
- Power blocking filter built-in
- Environmental protection to IP54
- Selectable output impedance (25, 50, 75,100 and 125Ω)
- 2ns pulse for near end fault location
- AUTO option selecting gain and pulse for each range
- AUTO option matches output impedance to cable
- Display distance in metres or feet
- Li-ion rechargeable battery (12 hours typical life)

SPECIFICATION

Except where otherwise stated, this specification applies at an ambient temperature of 20° C.

General

General			
Ranges:	Up to 20000	m with a minimum resolution of 0.1m	
	[More infoma	ition to come]	
Accuracy:	±1% of rang	$e \pm 1$ pixel at 0.67VF	
	[Note- The m	easurement accuracy is for the indicated	
	cursor positio	n only and is conditional on the velocity	
	factor being o	correct.]	
Resolution:	1% of range		
Input Protection	: This instrume	nt complies with IEC61010-1 for	
	connection to	live systems up to 150 V CAT IV.	
	Fused leads n	nust be used if the voltage between the	
	terminals exc	eeds 300 V.	
Output pulse:	up to 20 volt	s peak to peak into open circuit. Pulse	
		nined by range and cable	
Gain:	Set for each r	ange with user selectable steps (in	
	Manual opera	ating mode)	
Velocity Factor:	Variable from	0.2 to 0.99 in steps of 0.01	
TX Null:	Automatic		
Power Down:	User program	mable auto power off timer 1, 5, 10	
	mins or off		
Batteries:	-	eable battery with 12 hours typical life	
Safety:		nt complies with IEC61010-1 for	
		live systems up to 150 V CAT IV or	
		Fused leads must be used if the voltage	
		terminals exceeds 300 V. Compliant with	
		EN61010-3, UN38.3 and EN62133	
EMC:		h Electromagnetic Compatibility	
		(Light industrial) BS EN 61326-1, with a	
		formance of 'B' for all immunity tests	
Mechanical:		nt is designed for use indoors or	
		is rated to IP54.	
Case Dimensions:		4 in) x 190 mm (7.5 inches)	
	x 55 mm (2.2		
Instrument weig		8lbs)	
Case material:	ABS		
Connectors:	Four 4mm-safety terminals and two F connectors. Other standard push on adapters will fit the		
		rd push on adapters will fit the	
Testerie	TDR2000/3		
Test Leads:	-	consisting of 2 x 4mm shrouded	
	connector to miniature crocodile clips (TDR Bed-of-Nails lead set (CFL535G) or .5 metri		
Disalaria	leads (TDR2000/3P)		
Display:		kel WVGA colour graphics LCD, viewable wironments. User selectable colour	
		wironments. User selectable colour	
Environment	schemes		
Environment		15%C to + 50%C (5%E to 122%E)	
Operational Temperature:		-15°C to +50°C (5°F to 122°F)	
Charging Temperature:		0° C to 40° C	
Storage Temper	ature:	-20°C to 70°C (-4°F to 158°F)	

Megger.

ORDERING INFORMATION

Cat. No.			
6231-654			
1003-217			
1003-352			
6231-652			
0251-052			
1002-552			
1002-015			
-			

UK Archcliffe Road Dover CT17 9EN England T +44 (0) 1304 502101 F +44 (0) 1304 207342 UKsales@megger.com UNITED STATES 4271 Bronze Way Dallas TX 75237-1019 USA T 800 723 2861 (USA only) T +1 214 333 3201 F +1 214 331 7399 USsales@megger.com

OTHER TECHNICAL SALES OFFICES Valley Forge USA, College Station USA,

Valley Forge USA, College Station USA, Sydney AUSTRALIA, Danderyd SWEDEN, Ontario CANADA, Trappes FRANCE, Oberursel GERMANY, Aargau SWITZERLAND, Dubai UEA, Mumbai INDIA, Durban SOUTH AFRICA, Chonburi THAILAND, Malaga SPAIN CERTIFICATION ISO

Registered to ISO 9001:2008 Cert. no. Q 09250 Registered to ISO 14001-2004 Cert. no. EMS 61597

TDR2000/3_DS_en_V01 www.megger.com Megger is a registered trademark

INLEC, supporting you to deliver a world class service, every day, in every sector ...



OUR COMMITMENT TO YOU

A wealth of knowledge and experience.

You can take advantage of expert advice to ensure you get the best, most appropriate and cost effective equipment for the job. We supply a wide variety of industries, so if there is another way to do the job or save you time and money we'll pass on the benefit of our experience for free.

Honest advice, just a phone call away.

If we don't have a particular item, rather than hiring you something that won't do the job, we would rather direct you to an alternative supplier. You will always be provided with full instructions and if you still need help, call our technical team on Nationwide Low Call 0333 6000 600. Our aim is to save you time, frustration and money.

Top quality equipment from major manufacturers.

With Inlec you'll get the most accurate, reliable and wellmaintained equipment available. Prices are regularly reviewed to ensure you always enjoy the best value for money. We have made a significant investment in test equipment so we ensure that it's well packed to minimise damage and delay.

We really do listen to you.

You won't waste your time contacting Inlec. Every request for equipment is logged and carefully considered. Listening to our customers helps keep our product range up to date and relevant. If you are unhappy about any aspect of our service please let us know so we can put it right.

YOUR 5 WAY GUARANTEE

O GUARANTEE SAME DAY DESPATCH

We understand why prompt delivery is important to you. So, if we confirm your order before 3pm, you are guaranteed same day despatch.

2 OUR PRICE GUARANTEE

Inlec guarantee you real value for money. Our price match policy is simple - if you can hire the same product for less elsewhere, we guarantee to match that price and reduce it by a further 10% of the difference - and still deliver our industry leading technical and customer support.

For full details check our price-match guarantee online

O TOP QUALITY GUARANTEED

All equipment is thoroughly checked prior to dispatch to ensure you receive it in full, safe working order. Your shipment will be securely packed and include manufacturer's instructions, accessories or consumables and a valid calibration certificate where appropriate. In addition, Inlec offer a 24 hour replacement service if you decide the equipment is not suitable for your application*.

FRIENDLY, KNOWLEDGEABLE ADVICE GUARANTEED

Inlec are happy to provide you with free advice, from anunbeatable team of experienced, knowledgeable and friendly engineers and hire experts.

S YOUR GUARANTEE OF THE BEST CUSTOMER SERVICE

Throughout your hire we will work hard to ensure you enjoy the very best in support and service from Inlec. We guarantee you won't find better service anywhere in the industry.

*subject to availability and conditions

Europe's leading Test Equipment Hire Specialist



Nationwide Low Call 0333 6000 600 Online: www.inlec.com





Inlec UK Ellerbeck Way, Stokesley Business Park, Stokesley N Yorkshire TS9 5JZ United Kingdom