EUROPE'S LARGEST SELECTION OF TEST & MEASUREMENT EQUIPMENT FOR HIRE

INLEC.COM



Nationwide Low Call 0333 6000 600














n active element in electrical protection, the earthing is usually made up of several links to the equipotential surface (surface of the earth), thus forming multiple loops. To complement the traditional continuity and earth measurements, the C.A 6411, 6413 and 6415 offer the advantage of quick earth testing in total safety (the electrical installation remains connected to earth, even during the test). These clamps

can also be used to measure the leak currents flowing into the ground. To further optimize your testing operations, the C.A 6413 and 6415 models

also possess an alarm function (buzzer if threshold exceeded) and a measurement logging function. In the event of low earth resistances, the C.A 6415 allows measurements from one tenth of an Ohm upwards.

	Calibre (1)	Resolution	Accuracy (2)
	0.10 to 1.00 Ω ⁽³⁾	0.01 Ω	± (2 % + 0,02 Ω)
	1.0 to 50.0 Ω	0.1 Ω	$\pm (1.5 \% + 0.1 \Omega)$
Resistance	50.0 to 100.0 Ω	0.5 Ω	$\pm (2.0 \% + 0.5 \Omega)$
measurement	100 to 200 Ω	1 Ω	± (3.0 % + 1 Ω)
	200 to 400 Ω	5 Ω	± (6.0 % + 5 Ω)
	400 to 600 Ω	10 Ω	$\pm (10 \% + 10 \Omega)$
	600 to 1200 Ω	50 Ω	-
DAAC	1 to 300 mA	1 mA	± (2.5 % + 2 mA)
RMS current	0.300 A to 3.000 A	1 mA	± (2.5 % + 2 mA)
measurement	3.00 A to 30.00 A	10 mA	(2.5 % + 20 mA)



(3) Calibre only available on the C.A 6415 model



measure



General specifications

- Olamping diameter: 32 mm
- Temperature of use: -10 to +55 °C
- Storage temperature: -30 to +70 °C
- Relative humidity: 0 to 75% RH
- IP 30 as per EN 60529
- Dimensions : 235 x 100 x 55 mm
- C.A 6413 and 6415 models:
 Alarm threshold adjustable from 1 to 199
 Memory capacity: 99 measurements.

Electrical specifications

- Complies with EN 61010-2-032
- Dual insulation, class 2
- 150 V, cat. III, pollution level 2
- Max. over-intensity: 100 A AC constant
- Measurement frequency:
 1689 Hz (C.A 6411 and C.A 6413)
 2400 Hz (C.A 6415)
- Charge life: with 9 V alkaline battery (Cd/Ni battery accepted):
 - 1000 thirty-second measurements (C.A 6411 and C.A 6413)
 - 1500 thirty-second measurements (C.A 6415)



To order


C.A 6411 P01. 1220.01
C.A 6413 P01. 1220.02
C.A 6415 P01. 1220.03

Each earth clamp is delivered in a carrying case with one 9 V battery and a user's manual.

Calibration loop

CL1P01. 1223.01

Your distributor



C.A 6411, 6413 and 6415 models

Q Resistance measurement

m A Current measurement

 $\mbox{100}\%$ Remaining battery charge life

Battery indicator

Automatic shutdown inhibited

HOLD Holding of display

• III Buzzers active

NOISE Significant eddy currents

Jaws not closed properly

C.A 6411 and 6413 models

R<1Ω Resistance under 1 Ω

C.A 6413 and 6415 models

₽188 Alarm function

MEM Recording in memory

■ 88 Reading memory



C.A 6411 model

ON OFF Start/stop + autotest

 Ω Resistance measurement

A Current measurement



C.A 6413 and 6415 models

OFF Start/stop + autotest

 Ω Resistance measurement

A Current measurement

MEM Recording of measurement
AL Alarm activation and adjustment



INLEC, supporting you to deliver a world class service, every day, in every sector ...













OUR COMMITMENT TO YOU

A wealth of knowledge and experience.

You can take advantage of expert advice to ensure you get the best, most appropriate and cost effective equipment for the job. We supply a wide variety of industries, so if there is another way to do the job or save you time and money we'll pass on the benefit of our experience for free.

Honest advice, just a phone call away.

If we don't have a particular item, rather than hiring you something that won't do the job, we would rather direct you to an alternative supplier. You will always be provided with full instructions and if you still need help, call our technical team on Nationwide Low Call 0333 6000 600. Our aim is to save you time, frustration and money.

Top quality equipment from major manufacturers.

With Inlec you'll get the most accurate, reliable and well-maintained equipment available. Prices are regularly reviewed to ensure you always enjoy the best value for money. We have made a significant investment in test equipment so we ensure that it's well packed to minimise damage and delay.

We really do listen to you.

You won't waste your time contacting Inlec. Every request for equipment is logged and carefully considered. Listening to our customers helps keep our product range up to date and relevant. If you are unhappy about any aspect of our service please let us know so we can put it right.

YOUR 5 WAY GUARANTEE

1 GUARANTEE SAME DAY DESPATCH

We understand why prompt delivery is important to you. So, if we confirm your order before 3pm, you are guaranteed same day despatch.

OUR PRICE GUARANTEE

Inlec guarantee you real value for money. Our price match policy is simple - if you can hire the same product for less elsewhere, we guarantee to match that price and reduce it by a further 10% of the difference - and still deliver our industry leading technical and customer support.

For full details check our price-match quarantee online

3 TOP QUALITY GUARANTEED

All equipment is thoroughly checked prior to dispatch to ensure you receive it in full, safe working order. Your shipment will be securely packed and include manufacturer's instructions, accessories or consumables and a valid calibration certificate where appropriate. In addition, Inlec offer a 24 hour replacement service if you decide the equipment is not suitable for your application*.

FRIENDLY, KNOWLEDGEABLE ADVICE GUARANTEED

Inlec are happy to provide you with free advice, from anunbeatable team of experienced, knowledgeable and friendly engineers and hire experts.

9 YOUR GUARANTEE OF THE BEST CUSTOMER SERVICE

Throughout your hire we will work hard to ensure you enjoy the very best in support and service from Inlec. We guarantee you won't find better service anywhere in the industry.

*subject to availability and conditions

Europe's leading Test Equipment Hire Specialist









