



EUROPE'S

LARGEST SELECTION

윾

80

MEASUREMENT EQUIPMENT FOR

HIRE



880PL-DC

Digital DC Hipot Tester - 80kV





■ The **880PL-DC** DC Hipot is a modern solution for testing the insulation strength of electrical apparatus. Outfitted with a state-of-the-art digital interface and extensive safety features, the 880PL-DC ensures simplistic operation, accurate results, and operator safety under all circumstances.

The 880PL-DC features the most accurate kilovoltmeter readings regardless of load current. Voltage measurements are taken directly at the output of the high voltage transformer, while current is measured at the return leg to ensure the highest accuracy. Output power is created through a full-wave, voltage multiplier.


APPLICATIONS


- Power Cable
- Transformers
- Electrical Switchgear / Vacuum Interrupters
- Motors/ Generators
- Aerial Lift Equipment / Bucket Trucks
- Insulated Electric Apparatus & Components



- ☑ DC hipot test up to 80kV, 10mA
- ☑ Lightweight, rugged design for field use (57 lbs / 25.8kg)
- Measures output voltage, leakage current, insulation resistance (IR), and polarization index (PI)
- Adjustable test parameters such as target voltage, maximum leakage, ramp rate, and dwell time
- ☑ Recorded test results and data transfer via USB 2.0
- ☑ Full-wave voltage multiplier
- Safe operation with interlock, emergency stop, and battery backup for display meters if input power is lost
- ☑ Internal discharge solenoid

MODES OF OPERATION













TECHNICAL SPECIFICATIONS

880PL-DC 19.45" L x 13.7" W x 20" H 57 lbs (25.8 kg) 14122° F (-1050°C) -4158° F (-2070°C) 595% non-condensing	49.4 x 34.8 x 50.7 cm
57 lbs (25.8 kg) 14122° F (-10 50°C) -4158° F (-20 70°C) 595% non-condensing 90-264VAC, 45-65Hz, 900VA	49.4 x 34.8 x 50.7 cm
14122° F (-10 50°C) -4158° F (-20 70°C) 595% non-condensing	
-4158° F (-20 70°C) 595% non-condensing 90-264VAC, 45-65Hz, 900VA	
-4158° F (-20 70°C) 595% non-condensing 90-264VAC, 45-65Hz, 900VA	
595% non-condensing 90-264VAC, 45-65Hz, 900VA	
90-264VAC, 45-65Hz, 900VA	
100 80 000 VDC	
100 00 000 \/DC	
100-60,000 VDC	
10mA	
Negative Output, Positive Ground	
10 kΩ8 GΩ	
Resolution	Accuracy
100 V	±0.5% of full scale
0.1 μΑ	±1% of scale (100µA, 10mA)
10 kΩ	±1% of scale
Emergency Stop	Visual Warning Indicators
External Interlock	Audible Warning Indicator
Interlock Hand-switch	External Warning Lamp (optional)
Interlock Foot Pedal (optional)	Battery Backup for Display Metering
7" TFT, 800 x 480, Color Touch Screen,	High Brightness (Adjustable)
USB 2.0 for Memory Stick	
CSV	
1 year recommended	
	Negative Output, Positive Ground 10 k Ω 8 G Ω Resolution 100 V 0.1 μ A 10 k Ω Emergency Stop External Interlock Interlock Hand-switch Interlock Foot Pedal (optional) 7" TFT , 800 x 480, Color Touch Screen, USB 2.0 for Memory Stick CSV

SCOPE OF SUPPLY

25ft HV Output Cable with Clamp 25ft HV Return Cable with Clamp 25ft HV Ground Cable with Clamp 15ft HV Ground with Clamp 6ft Input Power Cord Interlock Plug Interlock Hand-switch Operations Manual Calibration Certificate

OPTIONAL ACCESSORIES



OFFICES:

Europe Haefely Test AG Birsstrasse 300 4052 Basel Switzerland

2 + 41 61 373 4111

플 + 41 61 373 4912

₹ sales@haefelv.com

China Haefely Test AG Representative Beijing Office 8-1-602, Fortune Street No. 67, Chaoyang Road, Chaoyang District Beijing, China 100025

> **2** +86 10 8578 8099 ± +86 10 8578 9908 ₹ sales@haefelv.com.cn

North America Hipotronics, Inc. 1650 Route 22 N Brewster, NY 10509 United States

2 +1 845 279 3644 **≝** +1 845 279 2467

sales@hipotronics.com

Standard Warranty is 1 year

HAEFELY HIPOTRONICS has a policy of continuous product improvement. We therefore reserve the right to change design and specification without notice



Nationwide Low Online: wv

Europe's

leading

Test

Ш

quipme

2 Hire

S

pecialist

5 WAY

OUR COMMITMENT TO YOU

GUARANTEE









deliver every

മ

world

sector