INLEC.COM



Nationwide Low Call 0333 6000 600

Portable Vibration Shakers

HI 803/813 Shakers



HI 803/813 portable vibration shakers are designed to be used in the field or shop to verify the performance of vibration transducers, connectors, cabling, instruments or permanently installed condition monitoring systems. Both models are battery-powered, portable and feature a built-in reference accelerometer and indicator with calibration traceable to the National Institute of Standards and Technology (NIST).

These shakers can easily check velocity transducers, accelerometers and non-contacting Eddy Probe displacement measurement systems. Simply attach the transducer to the shaker head (displacement probes require a mounting fixture and target), set the shaker to a known vibration reference level, and verify readings. The reference test level can be set in acceleration, velocity, or displacement, English or Metric.

Features

- Actual precision vibration testers
 True and accurate testing of vibration sensors
- NIST traceable calibration reference
 High-level vibration accuracy
- High-level vibration accuracy
- Variable frequency and adjustable vibration amplitudes
 Rapid set-up for all vibration conditions
- Battery operated
 Ability to "take the calibration lab to the field"

Applications

- Loop checks of vibration monitoring systems
- Verification and testing of velocity transducers, accelerometers, eddy current probes, etc.
- Troubleshooting of issues in vibration monitoring loops
- Calibration of portable vibration analyzers
- Confirmation of vibration alarms

Specifications

	Model HI 803	Model HI 813
Battery Type	Sealed, rechargable	Sealed, rechargable
Charger	Internal	Internal
	Specify 120 or 240 Vac	120 or 240 Vac
Frequency Range	10 to 10,000 Hz	25 to 10,000 Hz
Acceleration Readout	10 to 2,000 Hz, ±.3 dB	30 to 1,000 Hz, <u>+</u> .3 dB
(<u>+</u> 1 digit)	2,000 to 10,000 Hz, +1 dB	1,000 to 10,000 Hz, +1 dB
Velocity Readout	10 to 500 Hz, +.3 dB	30 to 500 Hz, +.3 dB
Displacement Readout	25 to 200 Hz, +.3 dB	30 to 100 Hz, +.3 dB
Maximum Output	10g at 100 Hz, 100 gram load	10g at 100 Hz, 100 gram load
	(3g above 1,000 Hz)	(3g above 1,000 Hz)
	1g at 100 Hz, 750 gram load	1g at 100 Hz, 750 gram load
Calibration	NIST traceable standard	NIST traceable standard
Waveform Distortion	<5% THD, 30 to 2,000 Hz	<5% THD, 30 to 2,000 Hz
Reference Output	50 mV/g	50 mV/g
Maximum Unsupported	750 grams, vertical	750 grams
Load	or 500 grams, horizontal	vertical or horizontal
Physical Size & Weight	11"W x 7"D x 10"H, 21 lbs.	11"W x 7"D x 10"H, 19 lbs.
Sensor Mounting Thread	1/4-28 thd hole, 1/4" deep	1/4-28 thd hole, 3/8" deep
English & Metric Readout	Yes	Yes
Indicates Test Sensor	Yes, normalized sensitivity	No
Output	mass loading	
	compensation, phase	
Internal Memory	Yes, stores test data	No
Built-In Printer	Yes, thermal type, prints	No
	current or stored test data	
RS-232 Output	Yes, stored data transfer	No




Portable Vibration Shakers


HI 803/813 Shakers

How to Select

Model	Description
HI 803-120V	Portable Shaker, variable frequency and amplitude control, manual and sensitivity modes (sensitvity mode tests the transducer and provides a mV/unit output to compare with the sensor manufacturer's specifications), built-in self-test program, built-in printer with paper, data storage, RS-232 port and data transfer software, 120V, standard accessories, CE Approved.
HI 803-240V	Same as the HI 803-120V, except the voltage requirement is 240 volts.
HI 813-CE	Portable Shaker, variable frequency and amplitude control, 115/220V, standard accessories, CE Approved.



HI 803 Panel



HI 813 Panel

Accessories

Power Cord, AC
Screw, 1/4-28X
Mounting Fixture, Accelerometer
Screwdriver, Flat Blade
Diskette, Communication Software
Mounting Spacer*
Cable Connector Kit, HI 803 input from TUT
Cable, Portable Shaker to 2-pin HI 113 Accel
Cable, Portable Shaker to BNC Accel*
Paper, Thermal Printer (Seiko p/n 201-211-25C)
HI 803 Calibration Kit*
Power Cord, AC
Velocity/Universal Transducer Adapter, w/screw
Mounting Fixture/Dial Micrometer, Kit, Eddy
Probe Test, English*

HI 223-M	Mounting Fixture/Dial Micrometer, Kit, Eddy
	Probe Test, Metric*
HI 224	Mounting Bar Fixture, Kit, Eddy Probe Test*
0228-0136-01	Mounting Plate, Magnetic 2" Dia, 1/4" thick*
0228-0070-01	Stud, 1/4-28 to 1/4-28 UNF
0228-0070-02	Stud, 1/4-28 to 10-32 UNF*
0228-0141-01	Stud, 1/4-28 to M8 (Metric)*
0228-0137-01	Adapter stud. 1/4-28 UNF to 3/8-24 (HI 5701VT)*
0228-0070-03	Bushing, 1/4-28 to 2-56 UNC
0228-0070-04	Bushing, 1/4-28 to 6-32 UNC
0228-0070-05	Bushing, 1/4-28 to 10-32 UNC
0228-0075-01	4140 Steel Target (incl w/ 223/224 kits)*
0228-0071-02	Velocity/Universal Transducer Adapter, w/screw*
0228-0072-01	Wrench, Shaker Head
0215-0183-01	Charge Cable

*Indicates a non-standard accessory.



INLEC, supporting you to deliver a world class service, every day, in every sector ...













OUR COMMITMENT TO YOU

A wealth of knowledge and experience.

You can take advantage of expert advice to ensure you get the best, most appropriate and cost effective equipment for the job. We supply a wide variety of industries, so if there is another way to do the job or save you time and money we'll pass on the benefit of our experience for free.

Honest advice, just a phone call away.

If we don't have a particular item, rather than hiring you something that won't do the job, we would rather direct you to an alternative supplier. You will always be provided with full instructions and if you still need help, call our technical team on Nationwide Low Call 0333 6000 600. Our aim is to save you time, frustration and money.

Top quality equipment from major manufacturers.

With Inlec you'll get the most accurate, reliable and wellmaintained equipment available. Prices are regularly reviewed to ensure you always enjoy the best value for money. We have made a significant investment in test equipment so we ensure that it's well packed to minimise damage and delay.

We really do listen to you.

You won't waste your time contacting Inlec. Every request for equipment is logged and carefully considered. Listening to our customers helps keep our product range up to date and relevant. If you are unhappy about any aspect of our service please let us know so we can put it right.

YOUR 5 WAY GUARANTEE

1 GUARANTEE SAME DAY DESPATCH

We understand why prompt delivery is important to you. So, if we confirm your order before 3pm, you are guaranteed same day despatch.

OUR PRICE GUARANTEE

Inlec guarantee you real value for money. Our price match policy is simple - if you can hire the same product for less elsewhere, we guarantee to match that price and reduce it by a further 10% of the difference - and still deliver our industry leading technical and customer support.

For full details check our price-match guarantee online

3 TOP QUALITY GUARANTEED

All equipment is thoroughly checked prior to dispatch to ensure you receive it in full, safe working order. Your shipment will be securely packed and include manufacturer's instructions, accessories or consumables and a valid calibration certificate where appropriate. In addition, Inlec offer a 24 hour replacement service if you decide the equipment is not suitable for your application*.

FRIENDLY, KNOWLEDGEABLE ADVICE GUARANTEED

Inlec are happy to provide you with free advice, from anunbeatable team of experienced, knowledgeable and friendly engineers and hire experts.

5 YOUR GUARANTEE OF THE BEST CUSTOMER SERVICE

Throughout your hire we will work hard to ensure you enjoy the very best in support and service from Inlec. We guarantee you won't find better service anywhere in the industry.

*subject to availability and conditions

Europe's leading Test Equipment Hire Specialist









