aegex10[™] intrinsically safe tablet

ae(

Aegex Technologies provides intrinsically safe solutions for the world's most hazardous industrial operations in oil and gas, chemical, mining, pharmaceutical, public safety, utilities and other industries with explosive environments. Aegex solutions bring real-time connectivity to hazardous areas, helping organizations harness the power of data to optimize efficiency, safety and productivity.



The **aegex10**[°] **Intrinsically Safe Tablet** is the most advanced, low-cost, lightweight and rugged Windows tablet that is purpose-built for **Zone 1 / Division 1 hazardous areas.** Simple to deploy, it is the basis for an industrial Internet of Things platform for hazardous industries, allowing operations to easily begin their digital transformation to Industry 4.0.

Purpose-Built Intrinsically Safe and Enterprise-Class: Aegex devices are certified UL913, C I, II, III D1, ATEX IECEx Zone 1 and IP65 for HazLoc use.

- Cloud-Based Data Sharing: Aegex solutions use 4G LTE or Wi-Fi for real-time collaboration.
- Enterprise-Class Security with Intel Architecture: Aegex solutions rely on Intel McAfee Security suite for enterprise-wide protection.
- Customizable Solutions for All Hazardous Zones and Jobs: Build your own solution for each team member with Aegex enterprise applications.



```
ATEX Zone 1
IECEx Zone 1
UL Class I, II, III Division 1
```

10.1" WUXGA Display

Powered by Intel Atom Quad Core

Windows 10

Intel Security Suite



aegex.com



	UL913 5 th edition: C I, II, III Div 1 Gr A-G T4, T _{amb} = -10°C+50°C CI Z0 Gr IIC T4 IP65, T _{amb} = -10°C+50°C CAN/CSA-22.2 Part 157
Intrinsically Safe Certifications	IECEx 60079-0 & -11: Ex ib IIC T6 Gb, T _{amb} = -10°C+50°C Ex ib IIIC T85°C Db IP6X, T _{amb} = -10°C+50°C Ex ib I Mb, Tamb = -10°C+50°C
	ATEX 60079-0 & -11:
Exterior	Dimensions: 273 x 185 x 16.8 mm (10.75 x 7.28 x 0.66 in) Weight: 980 grams (2.16 lbs) IP65
Display	Screen: 10.1" AHVA Full HD Plus Resolution: 1920 x 1200 Capacitive touch: Multi-touch
	Contrast 800:1 Viewing angle (up/down, left/right) 170°
Battery Life	Up to 12 hours of web browsing (Battery: 3.8V, 8700mAh, 33Wh)
Charging time (in standby)	Docking station: 0-90% in 2.5hours, to 100% in approx. 3.5 hours USB charger: 0-90% in 4hours, to 100% in approx. 5.5 hours
Storage/RAM	128GB storage / 4GB RAM
CPU & Wireless	Intel® Quad-Core Atom processor 2.39GHz*, 4G LTE available Wi-Fi 802.11ac/802.11 a/b/g/n dual band (2.4GHz and 5GHz) Bluetooth® 4.0 Low Energy technology NFC & RFID (HF: 13.56MHz)** Intel Wireless Display
Location	GPS / GLONASS (cold start <30s, warm start < 5s)
Ports	Full-size USB 2.0 USB 3.0, Ethernet, and HDMI on system connector Micro USB for charging Charging pads (12V) microSDXC™ card slot (supports up to 2TB) Headset jack
Software	Windows 10 Pro, Windows 10 Enterprise
Cameras, Video & Audio	8.0 megapixel autofocus rear-facing camera with flash, full HD video 2.0 megapixel front-facing camera full HD video Front and rear microphones Stereo speakers
Sensors	Ambient light sensor, Accelerometer, Gyroscope, E-Compass, SAR proximity sensor
Security	Silicon Level, Intel Security (SMEP, PPDRNG, fTPM, and TPM 2.0) Software Level Device Control Windows 10 Mobile Device Management BitLocker
In the box	aegex10 [∞] intrinsically safe tablet Wall charger (power supply + USB cable)

To request a demo or to talk to a product specialist, please contact our nearest office or go to:

www.aegex.com

UNITED STATES HEADQUARTERS LOCATION Phone: +1 (470) 242-4000 Email: contact@aegex.com EUROPE (NETHERLANDS) LOCATION Phone: +31 10 808 1090 Email: contact@aegex.com EUROPE (UK) LOCATION Phone: + 44 2380 302 456 Email: contact@aegex.com

MIDDLE EAST (UAE) LOCATION

Phone: +971 4 813 7820 Email: contact@aegex.com

Distribution and resale around the globe. Visit aegex.com for more information.



contact@aegex.com



© 2017 Aegex Technologies, LLC. All Rights Reserved. The trademarks, logos, and service marks ("Marks") included herein are the property of Aegex Technologies, LLC or of their respective owners. AEGEX, AEGEX TECHNOLOGIES, aegex.com, and the Aegex logo are all trademarks of Aegex Technologies, LLC and/or its affiliates. Use of any Mark is not permitted without the prior written consent of Aegex Technologies, LLC or of the respective owner. The information in this document is subject to change without notice. Aegex and/or its representatives cannot be held responsible for any errors or inaccuracies within this document.

*Base Frequency 1.59 GHz, Burst Frequency 2.39 GHz

**P2P: ISO 18092, Reader/Writer: ISO 14443 –A-B, MIFARE, FeliCa®, ISO 15693, NFC Forum Tag Types 1 to 4 Card emulation: ISO 14443 –A-B-B', MIFARE, FeliCa RF, Distance up to 3 cm