



MINIFLOW RAPID

Cable blowing machine for access network

Rugged stainless construction

The machine is designed based on functionality including:

- Safety chain guard
- Adjustable knobs
- Push force indicator

Fast cable blowing

The machine is capable of installing fiber cable at a speed up to 100 m/min. and up to a distance of 3.5 km making it a compact and efficient cable blowing machine.

Built-in electronic counter and tachometer

The counter is easy to read, robust and simple to operate.

Robust and compact

The machine is constructed in stainless steel and anodized aluminium, which makes it suited for use under rugged conditions at cable blowing locations.

Flexible

The machine can quickly be adapted to accommodate different cable and duct sizes making it flexible to fit every fiber blowing job.


DON'T FORGET TO ORDER

Hydraulic Power Pack/Control valve and high pressure compressor.

Item No.: 101-10102 & 101-10103

Cable damage safety

MiniFlow RAPID has a unique monitoring system, which continuously monitors the pushing force applied on the fiber cable. This makes it easy to stop the process before any damage happens to the cable.



SPECIFICATIONS

Item No.:	101-10031
Cable diameter ¹ :	3-12 mm
Duct diameter:	7-20 mm
Blowing distance ² :	Up to 3500 m
Blowing speed ² :	Up to 100 m/min
Pushing force:	0-40 kg
Recommended pressure and airflow ³ :	8-16 bar (1,000 l/pr. min.)
Weight:	24 kg
Length:	650 mm
Width:	225 mm
Height:	210 mm

¹) Two sets of chains needed (3-8 mm/4-12 mm).

²) Depending on type of microduct and cable.

³) Cooled and dried air.