

Datasheet



0370 330 6021 www.sunbeltrentals.co.uk



376 True-rms AC/DC Clamp Meter with iFlex™

Work horse clamps with increased performance and flexibility

The new Fluke 376 Clamp Meter offers improved performance perfect for a wide range of current measurement situations. With true-rms ac voltage and current measurements, the Fluke 376 can read up to 1000 V and 1000 A in both ac and dc modes. Additionally, the Fluke 376 includes the new iFlex™ flexible current probe expanding the measurement range to 2500 A ac while providing increased display flexibility, ability to measure around awkward sized conductors and improved wire access. The Fluke 376 is the direct replacement for the Fluke 337 Clamp Meter.



Technical Data

Measurement capability

- 1000 A ac and dc current measurement with fixed jaw
- 2500 A ac current measurement with iFlex[™] flexible current probe
- 1000 V ac and dc voltage measurement
- True-rms ac voltage and current for accurate measurements on non-linear signals
- Frequency measurement to 500 Hz with both jaw and iFlex[™]
- 60 kΩ resistance measurement with continuity detection
- Min, max, average and inrush recording to capture variations automatically
- 500 mV dc measurement range to interface with other accessories
- 1000 µF capacitance measurement

Features

- iFlex[™] flexible current probe expands the measurement range to 2500 A ac while providing increased display flexibility, ability to measure awkward sized conductors and improved wire access
- CAT IV 600 V, CAT III 1000 V safety rating
- Integrated low pass filter and state of the art signal processing allows for use in noisy electrical environments while providing stable readings



- Proprietary inrush measurement technology to filter out noise and capture motor starting current exactly as the circuit protection sees it
- Ergonomic design fits in your hand and can be used while wearing personal protective equipment
- Large, easy to read, backlight display automatically sets the correct measurement range so you do not need to change switch positions while taking a measurement
- Three-year warranty
- Soft carrying case

Specifications

Fluke 376	Range	Resolution	Accuracy
AC current via jaw	999.9 A	0.1 A	$2\%\pm 5$ digits
AC current via iFlex™	2500 A	0.1 A	$3\%\pm 5$ digits
DC current	999.9 A	0.1 A	$2 \% \pm 5 \text{ digits}$
AC voltage	1000 V	0.1 V	1.5 $\% \pm$ 5 digits
DC voltage	1000 V	0.1 mV	$1 \% \pm 5$ digits
Resistance	60,000 Ω	0.1 Ω	$1 \% \pm 5$ digits
Frequency	500 Hz	0.1 Hz	0.5 $\%\pm5$ digits
Capacitance	1000 µF	1 μF	$1 \% \pm 4 \text{ digits}$
True-rms	•		
Continuity	•		
Hold	•		
Backlight	•		
Min/Max/Avg	•		
Inrush	•		
Low pass filter	•		
18 in iFlex Flexible™ Current Probe	Included		
10 in iFlex Flexible™ Current Probe	Accessory		
Wire capacity	750 MCM or 2-500 MCM		
Safety rating	CAT III 1000 V, CAT IV 600 V		

Models	Feature Changes		
Old model: Fluke 337			
New model: Fluke 376	Includes all 337 features plus: • CAT IV 600 V, CAT III 1000 V • iFlex [™] 2500 A ac • 1000 V ac/dc	• mV dc • 60 kΩ • 1000 μF	
Old model: Fluke 336			
New model: Fluke 375	Includes all 336 features plus: • CAT IV 600 V, CAT III 1000 V • Optional iFlex ^{**} 2500 A ac • mV dc	• 60 kΩ • 1000 μF • Min/Max/Avg	
New model: Fluke 374	Includes all 336 features (except low pass filter) plus: • CAT IV 600 V, CAT III 1000 V	 Optional iFlex[™] 2500 Å ac 1000 μF Min/Max/Åvg 	
Old model: Fluke 335			
New model: Fluke 374	Includes all 335 features plus: • CAT IV 600 V, CAT III 1000 V • Optional iFlex ^{**} 2500 A ac	 600 A ac/dc 1000 μF Min/Max/Avg 	
New model: Fluke 373	Includes all 335 features (except inrush) plus:	 CAT IV 300 V, CAT III 600 V 1000 μF 	
Old model: Fluke 334			
New model: Fluke 374	Includes all 334 features plus: • CAT IV 600 V, CAT III 1000 V • Optional iFlex ^{**} 2500 A ac • True-rms	• 600 A ac/dc • 1000 μF • Min/Max/Avg	
New model: Fluke 373	Includes all 334 features (except inrush) plus: • CAT IV 300 V, CAT III 600 V	• True-rms • 1000 μF	
Old model: Fluke 333			
New model: Fluke 373	Includes all 333 features plus: • CAT IV 300 V, CAT III 600 V • True-rms	 600 A ac 6000 Ω 1000 μF 	

Ordering information

376 True-rms AC/DC Clamp Meter with iFlex[™]

Included

Clamp meter, 18-inch iFlex™ probe, test leads, soft case, users manual



Fluke. Keeping your world up and running.®

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Europe B.V. PO Box 1186, 5602 BD Eindhoven, The Netherlands

For more information call:

In the U.S.A. (800) 443-5853 or Fax (425) 446-5116 In Europe/M-East/Africa +31 (0) 40 2675 200 or Fax +31 (0) 40 2675 222 In Canada (800)-36-FLUKE or Fax (905) 890-6866 From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116 Web access: http://www.fluke.com

©2010 Fluke Corporation. Specifications subject to change without notice. Printed in U.S.A. 7/2010 3834948A D-EN-N

Modification of this document is not permitted without written permission from Fluke Corporation.

We are supporting you to deliver a world class service, every day, in every sector...

LOCATIONS

LONDON, HEATHROW

Sunbelt Rentals UK Test & Monitoring 242-252 London Road, Staines, London TW18 4JQ 0333 122 3126 www.sunbeltrentals.co.uk/find-a-depot/london-heathrow

REDCAR

Sunbelt Rentals UK Test & Monitoring Unit 5 Kirkleatham Business Park, Redcar TS10 5SQ 0370 330 6021 www.sunbeltrentals.co.uk/find-a-depot/teesside

STOKESLEY

Sunbelt Rentals UK Test & Monitoring 2 Ellerbeck Way, Stokesley Business Park, Stokesley, North Yorkshire TS9 5JZ 01642 718 900 www.sunbeltrentals.co.uk/find-a-depot/stokesley



www.inlec.com

Order Online with Next Day Delivery, Online Chat & Online Account Management



★ Trustpilot

View our trustpilot score \star \star \star

• HEATHROW



