

Datasheet





0370 330 6021 www.sunbeltrentals.co.uk





Advanced test equipment for high voltage proof and preventive maintenance testing of electrical apparatus +1.518.329.3275 | sales@hvinc.com | web:www.hvinc.com

PFT Series - AC High Voltage Test Set Model PFT-652CM(F) 0-65 kVac @ 2 kVA



Description

The PFT-652CM(F) AC Dielectric Test Set is one of many in the PFT Series line of AC portable field use hipots. These hipots provide continuously adjustable AC voltage typically used to provide a go/no-go, or pass/fail, AC over-voltage Withstand Test on high voltage apparatus, like switchgear, circuit breakers, reclosures, vacuum bottles, hot sticks, motor windings, bus duct, and any other equipment needing an AC voltage proof test. The PFT Series offers the most field portable, affordable, and easiest to use AC testers at this voltage and power. Higher kVA AC test sets and others designed for motor & generator testing are also available. These other lines offer corona free output for Partial Discharge and Tan Delta testing. Some are CE Certified like this model.





Other HVI Products include

Higher Power AC Test Sets
DC Hipot/Megohmmeters
Very Low Frequency (VLF) Hipots
Tan Delta & Partial Discharge for VLF
Oil Dielectric Testers Aerial Lift Testers
Cable Fault Locators AC/DC Dividers

Features

Like all High Voltage, Inc. products, the PFT-652CM(F) is designed with the latest in high voltage technology and offers more features and higher quality and reliability than others:

- CE Marked. Designed specifically to meet CE directives
- Simple, manual controls for familiarity and ease in operation
- Rugged case with cushioned handles and storage for leads
- Insulated Return Guard/Ground circuit to bypass stray currents
- Zero Start and External Interlock provision
- Two range voltmeter and three range current meter
- Automatic transit protected meters rated 100 uA for durability

Specifications

Model	PFT-652CM(F) (F suffix for 230 V input)
Input	120 V, 50/60 Hz, 16 amps or 230 V, 50/60 Hz, 8 amps
Output	0 - 65 kVac @ 30 mAac
Output Termination	Top mounted aluminum spinning
Duty	2 kVA 1 hour ON/1 hour OFF, 1.5 kVA Continuous
Distortion	< 5%
Kilovolt Meter - 3.5"	0 - 32.5/65 kVac rms, +/-2 % FS Accuracy
Current Meter - 3.5"	0 - 1.0 mA with /x1, x10, x100 multipliers, +/- 2%
Control Case HV Tank	17.5" w x 11" d x 11" h (44 x 28 x 28 cm) 12" w x 13" d x 13.5" h (31 x 33 x 35 cm)
Weight Controls HV Tank	32 lbs. (15 kg) – 120 V , 47 lbs. (21 kg) – 230 V 50 lbs. (23 kg) <i>Strap handle on top for carrying</i>
Output Leads ** Output lead not insulated for HV	2- Black Test Leads for Grounding 1- Red Test Lead for HV Output ** 1- RG/58U Coax for Guarded Return 1- Interconnect Cable from Controls to HV Tank

HIGH VOLTAGE, INC. 31

31 County Rt. 7A, Copake, NY 12516 • (518) 329-3275 • Fax: (518) 329-3271

E-Mail: sales@hvinc.com • Web: www.hvinc.com

PFT625CMF revA 07/16

We are supporting you to deliver a world class service, every day, in every sector...

LOCATIONS

LONDON, HEATHROW

Sunbelt Rentals UK Test & Monitoring

242-252 London Road, Staines, London TW18 4JQ 0333 122 3126

www.sunbeltrentals.co.uk/find-a-depot/london-heathrow

REDCAR

Sunbelt Rentals UK Test & Monitoring

Unit 5 Kirkleatham Business Park, Redcar TS10 5SQ 0370 330 6021

www.sunbeltrentals.co.uk/find-a-depot/teesside





STOKESLEY

Sunbelt Rentals UK Test & Monitoring

2 Ellerbeck Way, Stokesley Business Park, Stokesley, North Yorkshire TS9 5JZ 01642 718 900

www.sunbeltrentals.co.uk/find-a-depot/stokesley



www.inlec.com

Order Online with Next Day Delivery, Online Chat & Online **Account Management**





View our trustpilot score











