

Datasheet





0370 330 6021 www.sunbeltrentals.co.uk



The Metrohm High Voltage Indicator is a tough, compact, passive instrument that detects the presence of voltage in circuits up to 15kV A.C. It consists of a resistive element, neon indicator, hand guard, handle and earth lead.



Product Features

Indicates the presence of live voltage on circuits up to 15kV
A.C.Circuit redundancy for added safety
Suitable for discharging lines
Flashing neon display for clear indication
Supplied with proving unit
Small, compact unit suitable for
use in confined spaces
High immunity to interference fields
D.C. blocking version available
60° and 90° bent end adaptors available









Electrical

Dielectric Test:

Indicator

Operating Voltage: 0.2 to 15kV, rms, 50/60Hz Circuit Current: 0.4mA nominal at 15Kv

> 0.293mA nominal at 11kV 20kV, rms, 50Hz for 1

minute

The indicator will not be Spark Protection:

damaged as a result of spark discharges when making contact with the

conductor under test. The indicator and its

Bridging Protection: accessories will not cause

> flashover between line pairs of the installation or between line pairs of the

installation and ground.

Proving Unit

300V D.C. nominal Output Voltage:

2off C cells, IEC R14 or Batteries:

LR14

Battery Low Voltage: 2V DC nominal

Mechanical Specifaction

Indicator

Length: 485mm Diameter: 32mm 139mm Handle Length:

Hand guard Width: 100mm 600ams Weight:

Black rigid PVC/Clear Material:

Polycarbonate

Proving Unit

Length: 255mm Diameter: 37mm Weight: 400gms

Material: Black rigid PVC

Spirent Communications (Scotland) Ltd policy is one of continuous development and hence we reserve the right to change specifications/design without prior notice.







Registration 901309

INVESTOR IN PEOPLE

Carrying Satchel

550mm Length: Width: 130mm Depth: 130mm Weight: 500gms

Soft black PVC Material:

Environmental

Operational

Temperature Range: -5°C to +50°C Cold Temperature: To IEC 68-2-1 To IEC 68-2-2 Dry Heat: Damp Heat: To IEC 68-2-3 Vibration Test: To IEC 1243. Part 1.

clause 6.4.3 **Bump Test:** To IEC 68-2-29 **Drop Test:** To IEC 1243, Part 1,

clause 6.4.4

To IEC 1243, Part 1, Shock Resistance:

clause 6.4.5

LIST OF EQUIPMENT		
	PART NO.	WEIGHT
H.V. Indicator Tester c/w Earth Lead	FO356A	600gms
	cobs	
Earth Lead	DFH5008	250gms
Proving Unit	FO300A	400gms
•		
60° Bent End Adaptor	DFH5051	
90° Bent End Adaptor	DFH5050	
Carrying Satchel	CMP5017	500gms
Cleaning Kit	DDM5003	
Proving Unit Batteries	CEJ0000	
2 X HP11		
Complete Kit (A) comprising: H.V. Indicator, Earth Lead, Proving Unit, Cleaning Kit and Carrying Satchel	FO357A	1.5kg
Complete Kit (B) comprising:	FO357A + DFH5051	
Complete Kit (C) comprising:	FO357A + DFH5050	

We are supporting you to deliver a world class service, every day, in every sector...

LOCATIONS

LONDON, HEATHROW

Sunbelt Rentals UK Test & Monitoring

242-252 London Road, Staines, London TW18 4JQ 0333 122 3126

www.sunbeltrentals.co.uk/find-a-depot/london-heathrow

REDCAR

Sunbelt Rentals UK Test & Monitoring

Unit 5 Kirkleatham Business Park, Redcar TS10 5SQ 0370 330 6021

www.sunbeltrentals.co.uk/find-a-depot/teesside





STOKESLEY

Sunbelt Rentals UK Test & Monitoring

2 Ellerbeck Way, Stokesley Business Park, Stokesley, North Yorkshire TS9 5JZ 01642 718 900

www.sunbeltrentals.co.uk/find-a-depot/stokesley



www.inlec.com

Order Online with Next Day Delivery, Online Chat & Online **Account Management**





View our trustpilot score











