



Datasheet



0370 330 6021

www.sunbeltrentals.co.uk



PW636i

Universal Test System

Specifications

Voltage generators

Setting range	
4-phase ac(L-N)	4×0~300V
1-phase ac(L-L)	1×0~600V
dc (L-N)	4×0~±300V
Power	
4-phase ac (L-N)	4×75VA typ., at 300V 4×50VA guar., at 300V
3-phase ac (L-N)	3×100VA typ., at 300V 3×85VA guar., at 300V
1-phase ac (L-L)	1×200VA typ., at 600V 1×170VA guar., at 600V
dc (L-N)	4×100 W at ±300 V
Accuracy	
	error < 0.08 % rd.+0.02 % rg. guar., at 0~300 V
	error < 0.03 % rd.+0.01 % rg. typ., at 0~300 V
Ranges	
	300V
Resolution	
	10mV for 300Vac
Distortion	
	< 0.05 % typ., (< 0.1 % guar.)

Current generators

Setting range	
6-phase AC (L-N)	6×0~32A
3-phase AC (2L-N)	3×0~64A
1-phase AC (6L-N)	1×0~180A
dc (6L-N)	1×0~±180A
Power	
6-phase AC (L-N)	6×450VA typ. at 32A 6×400VA guar. at 32A
3-phase AC (2L-N)	3×800VA typ. at 64A 3×700VA guar. at 64A
1-phase AC (6L-N)	1×1200VA typ. at 180A 1×1000VA guar. at 180A
1-phase DC (6L-N)	1×1400W typ. at 90A 1×1000W guar. at 90A
Max compliance	
voltage (L-N) (L-L)	21Vpk/42Vpk
Accuracy	
	error < 0.15 % rd.+0.05 % rg. guar., at 0~32A
	error < 0.05 % rd.+0.02 % rg. typ., at 0~32A
Ranges	
	32A
Resolution	
	1mA
Distortion	
	< 0.05 % typ. (< 0.1 % guar.)

General

Frequency	
Sine signal	DC, 1~1000Hz
Transient signal	dc~10.0 kHz

Accuracy	±1ppm
Resolution	0.001 Hz

Phase	
Angle range	-360°~+360°
Accuracy	<0.05°typ., <0.1° guar.at 50/60Hz
Resolution	±0.001°

Auxiliary dc supply

Voltage range	0~300V
Power	88W at 110V, 176W at 220V, 150W at 300V
Accuracy	error < 0.1 % rg. typ. (< 0.5 % rg. guar.)

Power supply

Nominal input voltage	110~240Vac
Permissible tolerance	90~260Vac
Nominal frequency	50/60Hz
Permissible frequency	45~65Hz

Binary inputs Group1

Number	8
Input characteristics	0~400Vdc threshold or potential free
Sample rate	20kHz
Time resolution	50μs
Max. measuring time	infinite
Debounce/Deglintch time	0~25ms
Counting function	< 3kHz at pulse width>150μs
Galvanic isolation	8 galvanically isolated

Binary inputs Group2

Number	4
Input characteristics	0~+5Vdc or dry contact
Sample rate	100kHz
Time resolution	10μs
Max. measuring time	infinite
Debounce/Deglintch time	0~25ms
Max. counting frequency	100kHz
Pulse width	< 3μs
Threshold voltage	2V
Voltage hysteresis	0.8V
Max. input voltage	+5V

Binary outputs, semiconductor

Number	4 (rear side)
Type	semiconductor
Break capacity dc	Vmax: 300Vdc /Imax: 0.5A/Pmax: 150W
Update rate	100μs
Imax	0.5A

Binary outputs, relay

Number	4 (front side)
Type	Potential free relay contacts, software controlled
Break capacity ac	Vmax: 300Vac /Imax: 8A /Pmax: 2000VA
Break capacity dc	Vmax: 300Vdc /Imax: 8A /Pmax: 150W

DC voltage measuring inputs

Measuring range	0~±10V
Accuracy	error < 0.02% rg. typ. (< 0.05% rg. guar.)
Input impedance	100KΩ

DC current measuring inputs

Measuring range	0~±20mA
Accuracy	error < 0.02% rg. typ. (< 0.05% rg. guar.)
Input impedance	50Ω

In-built monitoring and recording

Monitoring	currents and voltage outputs
Recording	analog outputs, binary inputs/outputs status
Mode	real time monitoring, no external wiring is required
Recording length	16s

Low level outputs

Setting range	12×0~10Vpk
Max. output current	1mA
Accuracy	error < 0.025 % typ. (< 0.07 % guar.)at 1~10Vpk
Resolution	250μV
Distortion(THD+N)	< 0.05 % typ. (< 0.1 % guar.)
Connection	19 pin combination socket (rear side)

IEC61850 upgrade

Interpretation hardware is in-built. Please contact the supplier for options to activate the IEC61850 software support function

Environmental conditions

Operation temperature	0~+50°C
Storage temperature	-25~+70°C
Relative humidity	5~95% non - condensing
EMC (Emission)	IEC-61000-3-2/3
EMC (Immunity)	IEC 61000-4-2/3/4/5/6/11
Safety	IEC 61010-1

Others

PC connection	Ethernet, 10M/100M
External amplifier interface	Circular connector
Current booster interface	Circular connector
GPS interface	DB9/TTL
Ground Socket (earth)	4 mm banana socket; front side
Weight	20kg
Dimensions (W x H x D)	360 mm× 157mm× 427 mm



PONOVO POWER CO., LTD.

2F, 4Cell, Tower C, In Do Mansion, No.48A Zhichun Road, Haidian District Beijing, PR China (100098)
Tel. +86 (10) 8275 5151 (reception) Tel. +86 (10) 82755151 ext.8887
Fax. +86 (10) 8275 5151-8103 support@relaytest.com info@relaytest.com www.relaytest.com

We are supporting you to deliver
a world class service, every day,
in every sector...

LOCATIONS

LONDON, HEATHROW

Sunbelt Rentals UK Test & Monitoring

242-252 London Road, Staines, London TW18 4JQ

0333 122 3126

www.sunbeltrentals.co.uk/find-a-depot/london-heathrow

REDCAR

Sunbelt Rentals UK Test & Monitoring

Unit 5 Kirkleatham Business Park, Redcar TS10 5SQ

0370 330 6021

www.sunbeltrentals.co.uk/find-a-depot/teesside

STOKESLEY

Sunbelt Rentals UK Test & Monitoring

2 Ellerbeck Way, Stokesley Business Park, Stokesley, North Yorkshire TS9 5JZ

01642 718 900

www.sunbeltrentals.co.uk/find-a-depot/stokesley



www.inlec.com

Order Online with Next Day
Delivery, Online Chat & Online
Account Management



★ Trustpilot

View our trustpilot score



STOKESLEY  REDCAR

 HEATHROW

0370 330 6021
instrumentation@sunbeltrentals.co.uk
testequipment@sunbeltrentals.co.uk
www.sunbeltrentals.co.uk


SUNBELT
RENTALS