

Datasheet





0370 330 6021 www.sunbeltrentals.co.uk

sebaкмт

Teleflex T 30-E

Digital Time Domain Reflectometer for the fault location on low and medium voltage networks

Benefits

- Self-explaining menus automatic test modes
- Bright colour display for use even in direct sunlight
- Very high near-end-resolution
- ▶ Two signal inputs for direct line comparison

easy co by sebarint

Description

The digital TDR Teleflex T 30-E is designed for the location of low resistance faults and interruptions in low and medium voltage cables. The integrated battery power supply makes it an ideally suited instrument for field use.

When connected to a shock discharge generator and an ARM filter, the combination is best suited for pre-location of high resistance and intermittent faults.

The Teleflex T 30-E offers convenient operator support with online help and One-Button-Operation easyGO and it automatically shows the end of cable and fault distance in the ARM-Mode.

Even inexperienced users can easily locate faults with the "Step-by-Step Easy Mode". The operator is guided through the fault locating process. On the other hand, the "Expert-Mode" provides free access to all parameters for comprehensive fault locating even under difficult conditions.

The TDR Teleflex T 30-E can also be used for the direct remote control of the SPG 40 and for TE pinpointing with the PD LOC. For system integration the T 30-E is also available as 19" version.

Technical Features

- One-Button-Operation
- Very bright 10.4" VGA colour TFT display
- Quick-Steps Mode with automated test procedures
- Step-by-Step Easy Mode with online help guidance
- Expert Mode with selectable parameter feature
- Automatic far end indication and fault recognition with distance indication
- Arm, Impulse current (ICE) and Travelling wave method (Voltage decay)
- ▶ High resolution in the short range
- ► High dynamic range with distance related gain
- Display of 3 traces
- Zoom
- ► Memory for 100 traces
- Mains and battery operated. Rechargeable NiMh batteries
- Remote Controlling of the SPG40 Fault location System
- PD Pinpointing with the PD LOC System

Technical Data

 Range
 TDR 10 m ... 50 km

 Transient 20 m ... 100 km

 Pulse Width
 35 ns ... 4 μs

 Sampling rate
 200 MHz

Sampling rate 200 MHz
Time Base Accuracy ± 0.01 %

Display 10.4" VGA colour TFT display V/2 50 m/µs ... 150 m/µs

Direct L1, Direct L2, Comparison L1 / L2, Difference L1 – L2,

ARM-Mode, Impulse current method, Voltage decay

Memory 100 traces

Interface RS 232 for PC and USB for Printer, CAN Bus for SPG 40

Remote control

(110 V optional), 12 V DC 360 x 160 x 270 mm or 19"

Dimensions (W x H x D)

Weight

Modes

6 kg

Scope of Delivery

- ▶ TDR Teleflex T 30-E
- Cable set
- Operating manual

Options

T 30-E as 19" version Completing to fault location system with:

- Mains filter for location on live LV cables
- ▶ PD LOC Upgrade

We are supporting you to deliver a world class service, every day, in every sector...

LOCATIONS

LONDON, HEATHROW

Sunbelt Rentals UK Test & Monitoring

242-252 London Road, Staines, London TW18 4JQ 0333 122 3126

www.sunbeltrentals.co.uk/find-a-depot/london-heathrow

REDCAR

Sunbelt Rentals UK Test & Monitoring

Unit 5 Kirkleatham Business Park, Redcar TS10 5SQ 0370 330 6021

www.sunbeltrentals.co.uk/find-a-depot/teesside





STOKESLEY

Sunbelt Rentals UK Test & Monitoring

2 Ellerbeck Way, Stokesley Business Park, Stokesley, North Yorkshire TS9 5JZ 01642 718 900

www.sunbeltrentals.co.uk/find-a-depot/stokesley



www.inlec.com

Order Online with Next Day Delivery, Online Chat & Online **Account Management**





View our trustpilot score











