



Datasheet



0370 330 6021
www.sunbeltrentals.co.uk

MTO250 Transformer Ohmmeter



- Capable of testing transformers up to 1000 MVA
- DC test current up to 50 A maximum
- Integrated demagnetization feature
- Computer control and internal data storage
- Validates proper operation of on-load tap-changers
- Protected against accidental current lead disconnection (through potential leads)

DESCRIPTION

The MTO250 Transformer Ohmmeter is a line-operated, field-portable instrument designed specifically to measure the resistance of all types of magnetic windings safely and accurately. It tests transformers, shunt reactors, rotating machine windings and performs low resistance measurements on connections, contacts and control circuits.

The dual set of potential inputs enables the resistance measurement of either two primary, two secondary windings, or of a primary plus a secondary winding simultaneously. This dual reading, dual injection characteristic, is a highly efficient method of completing tests in a timely manner.

The MTO250 is useful for testing the winding plus contact resistance of LTC (Load Tap Changers) as well as assessing the “make-break” transition event. Operating the LTC to change taps while DC test current is applied helps validate proper make-break transition. This test diagnoses possible issues such as aggressive pitting, weak springs, and misalignment of contact mechanisms.

Load tap changers are the only moving part of a transformer, and as they are mechanical devices, are one of the most vulnerable parts of a transformer. Load tap-changers result in more failures and outages than any other component and so require frequent testing and attention to ensure reliable and safe operation.

Applying DC current to highly inductive objects is a potentially dangerous test. The MTO250 has multiple built in safety features for the protection of the end user, the asset under test and the MTO itself. The MTO safety features include auto discharge in the event of input power loss, automatic discharge in the event of inadvertent disconnection of a test lead, safety interlock which places test into discharge when interrupted, and an optional high voltage strobe which warns personnel of presence of a dangerous condition.

TYPICAL APPLICATIONS

The MTO250 Transformer Ohmmeter is used to:

- Perform field testing of CT, PT, power transformer windings and their associated tap changers, and motors/generators.
- Verify factory winding resistance test results.
- Perform factory heat run tests.
- Diagnose and pinpoint problems such as the presence of defects in transformers, such as loose connections, and poor tap changer operation.
- To validate proper “make-before-break” operation of load tap-changers (LTC).

LTC / CONTINUITY

In normal LTC operation, continuity between the internal LTC contacts is maintained throughout each complete transition (from one tap position to the next). To check for this continuity, the MTO250 continually monitors the transition currents, in high resolution, for each tap position, and any slight discontinuities are detected and reported.

AUTO CORE DEMAGNETIZATION

It is common for DC current used for winding resistance, and OLTC/ Continuity testing to magnetize the transformer core. If the core is left magnetized after the completion of test, it can cause numerous issues as noted below.

Core magnetization results in remnant flux that can affect the measurements of subsequent AC testing such as excitation current or sweep frequency response analysis and cause erroneous readings. Magnetized CT cores can cause accidental tripping of protective relays. In other cases, when power transformers with a magnetized core are put back in service excessive inrush currents can develop which can trip the protection system.

FEATURES AND BENEFITS

- 50 amp test current reduces test time on high current secondary windings by up to 10 times when compared to traditional 10A units.
- Internal data storage with nine internal sets (groups) of results, allowing for easier organization while in the field.
- Two channel digital displays allows for testing two windings at a time, improving traditional test time by 50% or more.
- Computer-aided test form guides operator through connections and tests for all single- and three-phase transformers via PC control or data download.
- Checks the contact and timing health of on-load tap changers.
- Patented universal kelvin clamps, with 4 in. (100 mm) adjustable jaws are available, eliminating the need for multiple types of lead clips. Each kelvin clamp also includes banana plugs for use of external probes for testing on terminal blocks.
- Built-in safety discharge circuit safely discharges the specimen when test is completed, if lead accidentally disconnects, or if power is lost.
- Automated "heat run" testing and report via PowerDB software.

REMOTE TAP CHANGER (OPTIONAL)

The RTC-1 is a manually operated remote tap controller designed to provide a more efficient method of controlling (on)load tap changer (LTC) while performing routine tests on power transformers. It removes the need to be physically close to the LTC while testing or to have a second person controlling the LTC while operating the testing instrument. A 30 ft (9 m) three-conductor cable is provided to allow proximity to the test instrument while performing testing and advancing tap positions as required throughout the test.



SPECIFICATION

Input

85-264 VAC, 47-63 Hz, 1500 VA

Output

User Selectable Current

Ranges 1 A / 10 A / 25 A / 50 A

Open Circuit Voltage 50 V DC

Resistance and Current Measurement/Display

Current Range (A)	Resistance Range (Ohms)	Resolution (Ohms)
50 A	10 $\mu\Omega$ to .04 Ω	0.0000001
50 A	0.04 Ω to 0.4 Ω	0.00001
25 A	10 $\mu\Omega$ to 0.08 Ω	0.0000001
25 A	0.08 Ω to 0.8 Ω	0.00001
10 A	10 $\mu\Omega$ to .2 Ω	0.000001
10 A	0.2 Ω to 2 Ω	0.0001
1 A	100 $\mu\Omega$ to 2 Ω	0.00001
1 A	2 Ω to 20 Ω	0.001

NOTE: Resistance range 20 Ω to 1,000 Ω has best accuracy of $\pm 0.5\%$

Typical Accuracy: $\pm 0.1\%$ reading, $\pm 0.1\%$ range

Best Resolution 0.1 $\mu\Omega$

Typical Accuracy: $\pm 0.1\%$ reading, $\pm 0.1\%$ range

Guaranteed Accuracy: $\pm 0.25\%$ reading, $\pm 0.25\%$ range (once current has stabilized)

Current Resolution: 4 digits

Current Accuracy: $\pm 0.25\%$, $\pm 0.25\%$ range

Computer Interface (for downloading results and computer control)

Via Ethernet port

Internal Data Storage

9 groups (1-9) 99 results per group

LTC Make-Break Transition Settings

2 mS, 20 mS, 50 mS, 80 mS

Safety/EMC/Vibration Conforms to the Requirements of:

EN61010-1 Safety

ISTA 1A Shipping

EN61326 EMC

Environmental

Operating: 14° F to 122° F (-10° C to 50° C)

Storage: -13° F to 158° F (-25° C to +70° C)

Relative Humidity: 0-90% non-condensing

Dimensions

8.5 H x 21.5 W x 13 D in
(216 H x 546 W x 330 D mm)

Weight

Unit: net 30 lb (13.6 kg)

Optional leads: net 29 lb (13 kg) (for 60 ft [18 m])

In optional transit case: net 96 lb (43.5 kg)

We are supporting you to deliver
a world class service, every day,
in every sector...

LOCATIONS

LONDON, HEATHROW

Sunbelt Rentals UK Test & Monitoring

242-252 London Road, Staines, London TW18 4JQ

0333 122 3126

www.sunbeltrentals.co.uk/find-a-depot/london-heathrow

REDCAR

Sunbelt Rentals UK Test & Monitoring

Unit 5 Kirkleatham Business Park, Redcar TS10 5SQ

0370 330 6021

www.sunbeltrentals.co.uk/find-a-depot/teesside

STOKESLEY

Sunbelt Rentals UK Test & Monitoring

2 Ellerbeck Way, Stokesley Business Park, Stokesley, North Yorkshire TS9 5JZ

01642 718 900

www.sunbeltrentals.co.uk/find-a-depot/stokesley



www.inlec.com

Order Online with Next Day
Delivery, Online Chat & Online
Account Management



★ Trustpilot

View our trustpilot score



STOKESLEY  REDCAR

 HEATHROW

0370 330 6021

instrumentation@sunbeltrentals.co.uk

testequipment@sunbeltrentals.co.uk

www.sunbeltrentals.co.uk

