



REFMATE-2-BASIC

Item Number 4688297

The REFMATE is the Digital Manifold for the professional refrigeration engineer. It communicates wirelessly with temperature clamps, pressure gauges, and the scale, and documents all measured values in the device during long-term measurements. All data can be interpreted and displayed via the app REF MESH. The latest refrigerant and firmware updates can be easily installed via PC.

- Patented analog display (US patent 9'448'140)
- Large 4.3" TFT display
- Indication of superheating and subcooling
- Intuitive control via robust push buttons
- High precision with accuracy class 0.5
- Flexible power supply (AA batteries or USB)
- Wireless communication with REF MESH App and other devices
- All mechanical components are available as spare parts
- Lockable for long-term measurements

Technical Data

Material	Aluminium Brass ABS TPE
Color	yellow (RAL 1023) green (RAL 6026)
Standards	CE / FCC / IC / RCM / RoHS / REACH
RoHS Conformity	Yes
Accuracy Class	0.5 (+/-0.5%)
Gas Connection	1/4" SAE
Pressure Scale	bar psi kPa MPa kg/cm2
Number of Ways	2-way
Operating Temperature Range	-4 -122 °F
Storage Temperature Range	-4 -140 °F

Acknowledged globally



Pressure Range	-14 - 870 psi
Ingression Protection	IP42
Resolution	0.001 bar, 0.5 psi, 1 kPa, 0.0001 MPa, 0.01 kg/cm2
Battery	4 x AA Alternative Power Supply USB Mirco-B
Operating Hours	50 h at low operation
Signal Range	300 ft
Functions	Superheat / Subcool, Digital / analogue display, Slave pointer, Pressure zeroing, Data logging, Tube error compensation, Refrigerant favorites Refrigerant update, Firmware update, Set pressure reference, Field calibration, Unit and language settings, Display brightness, Wireless connections, Commissioning date, Printscreens
Scope of Supply	2 wired temperature sensors Calibration Certificate Batteries Instruction manual Case
Packaging	Sturdy plastic case
Sensor type	K-type Piezo Sensor
Temperature measuring range	-40 - 257 °F
Temperature Units	°C °F
Temperature Accuracy	+/-1 K
Temperature Resolution	0.1 °C / 0.1 °F

Accessories

4681466	K-TYPE-CLAMP TC	Clamp thermocouple for REFMATE and DIGIMON
4687785	WIRELESS-CLAMP WTC	Temperature clamp for REFMATE and TAP

REFCO Manufacturing (US) Inc.

66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
Fax 413 733 9267

sales@refcoswiss.com

Certificate
ISO 9001 / ISO 14001

4688587	CCL-60-A-38010	Set of 3 charging hoses with access control valve, 60"/150 cm blue and red with access control valve A-38010, 1/4" SAE, yellow 1/4" SAE with CA ball valve
4688596	CCL-60-A-38410	Set of 3 charging hoses with access control valve, 60"/150 cm blue and red with access control valve A-38410, 5/16" SAE, yellow 1/4" SAE with CA ball valve
9881276	CCL-60	Set of 3 charging hoses, 1/4"SAE, 60"/150 cm blue, red & yellow, 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
4687668	CCL-60-N	Set of 3 charging hoses, 1/4"SAE, 60"/150 cm blue, red & yellow, with neoprene gaskets, 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
4493622	CA-CCL-60	Set of 3 charging hoses with ball valve 1/4" SAE, 60"/150 cm, blue, red & yellow, 1x straight 1/4" SAE, 1x straight with ball valve 1/4" SAE and core depressor
4668533	CCL-60-CA	Set of 3 charging hoses with ball valve, 1/4" SAE, 60"/150 cm blue, red & yellow, ball valve integrated in charging hose, 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
9884095	CCL-60-1/2"-20UNF	Set of 3 charging hoses, R410A/R32, 60"/150 cm blue & red: 1x straight 1/4" SAE, 1x bended 1/2"-20UNF (5/16" SAE) with core depressor, yellow: 1x straight 1/4" SAE, 1x bended 1/4" SAE with c
4682519	CA-CCL-60-1/2"-20UNF	Set of 3 charging hoses, R410A/R32, 60"/150 cm blue, red & yellow with ball valve
4688477	VCL-60-3/8"SAEx1/4"SAE	Vacuum hose 3/8" SAE x 1/4" SAE, 60"/150cm
4687412	HCL6-60-Y-N-1/4x1/4	Special suction and charging hose, yellow, 60"/150cm Inner diameter: 9.5mm (3/8"), connections: 2 x 1/4" SAE, without core depressor, with neoprene gaskets

Spare Parts

4687079	M2-7-SET-B+R	Replacement knobs
4687104	M2-10-95-R/2	Complete valve set, 2 pieces
4491018	M4-6-11	Sight glass assembly with 2 gaskets
4687951	A-31452-Y/3	Threaded Y-style, 3 pieces
4687785	WIRELESS-CLAMP	Temperature clamp for REFMATE and TAP

Acknowledged globally



WTC		
4681394	K-TYPE-SENSOR	External temperature sensor for REFMATE and DIGIMON
4681466	K-TYPE-CLAMP TC	Clamp thermocouple for REFMATE and DIGIMON
4687093	M4-6-04-R/4	Valve seat assemblies, 4 pieces
4662624	M4-6-04-R/10	Valve seat assemblies, 10 pieces
4493169	M4-6-11-T	Sight glass removal tool
4688082	REFMATE-CASE	Protection case for digital manifold REFMATE
4687995	REFMATE-HOOK	Replacement hook