



# Datasheet



0370 330 6021  
[www.sunbeltrentals.co.uk](http://www.sunbeltrentals.co.uk)



# AQMesh

Technical specification

## GASES

Sensor	Type	Units	Range <sup>#1</sup>	LOD	LOC <sup>#2</sup>	Precision <sup>#3</sup>	Accuracy <sup>#4</sup>
NO	Electrochemical	ppb or $\mu\text{g}/\text{m}^3$	0-6,700 ppb	<1 ppb	<5 ppb	>0.9	1 ppb
NO <sub>2</sub>	Electrochemical	ppb or $\mu\text{g}/\text{m}^3$	0-4,900 ppb	<1 ppb	<5 ppb	>0.85	4 ppb
NO <sub>x</sub>	Electrochemical	ppb or $\mu\text{g}/\text{m}^3$	0-11,600 ppb	<2 ppb	<10 ppb	>0.9	4 ppb
O <sub>3</sub>	Electrochemical	ppb or $\mu\text{g}/\text{m}^3$	0-1,700 ppb	<1 ppb	<5 ppb	>0.9	5 ppb
CO	Electrochemical	ppb or $\mu\text{g}/\text{m}^3$	0-8,000 ppb	<30 ppb	<50 ppb	>0.8	20 ppb
SO <sub>2</sub>	Electrochemical	ppb or $\mu\text{g}/\text{m}^3$	0-1,100 ppb	<2 ppb	<10 ppb	>0.7	20 ppb
H <sub>2</sub> S	Electrochemical	ppb or $\mu\text{g}/\text{m}^3$	0-10,000 ppb	<1 ppb	<5 ppb	>0.7	1 ppb
TVOC <sup>#11</sup>	Electrochemical	ppb	0-2,500 ppb	<10 ppb	<50 ppb	>0.95	0.05 ppm
CO <sub>2</sub>	NDIR	ppm or $\text{mg}/\text{m}^3$	0-5,000 ppm	<1 ppm	<1 ppm	>0.9	50 ppb
CH <sub>4</sub>	Laser	ppm	0-10,000 ppm	<1 ppm	<1 ppm	>0.95	1 ppm
CH <sub>4</sub>	NDIR	ppm	0-1,000,000 ppm	<50 ppm	<50 ppm	TBC	10% (<300 ppm)

## PARTICLES

Sensor	Type	Units	Range <sup>#1</sup>	LOD	Precision <sup>#3</sup>	Accuracy <sup>#4</sup>
PM1 <sup>#5</sup>	Optical particle counter	$\mu\text{g}/\text{m}^3$	0-100,000 $\mu\text{g}/\text{m}^3$	0 $\mu\text{g}/\text{m}^3$	>0.9	5 $\mu\text{g}/\text{m}^3$
PM2.5 <sup>#5</sup>	Optical particle counter	$\mu\text{g}/\text{m}^3$	0-150,000 $\mu\text{g}/\text{m}^3$	0 $\mu\text{g}/\text{m}^3$	>0.9	5 $\mu\text{g}/\text{m}^3$
PM4 <sup>#5</sup>	Optical particle counter	$\mu\text{g}/\text{m}^3$	0-225,000 $\mu\text{g}/\text{m}^3$	0 $\mu\text{g}/\text{m}^3$	>0.9	5 $\mu\text{g}/\text{m}^3$
PM10 <sup>#5</sup>	Optical particle counter	$\mu\text{g}/\text{m}^3$	0-250,000 $\mu\text{g}/\text{m}^3$	0 $\mu\text{g}/\text{m}^3$	>0.85	5 $\mu\text{g}/\text{m}^3$
PM_Total <sup>#5</sup>	Optical particle counter	$\mu\text{g}/\text{m}^3$	0-350,000 $\mu\text{g}/\text{m}^3$	0 $\mu\text{g}/\text{m}^3$	>0.85	5 $\mu\text{g}/\text{m}^3$

## ADDITIONAL SENSORS

Sensor	Type	Units	Range <sup>#1</sup>	LOD	Precision <sup>#3</sup>	Accuracy <sup>#4</sup>
Pod temperature	Solid state	°C or °F	-20°C to 100°C	0.1°C	>0.9	2°C
Pressure	Solid state	mb	500 to 1500 mb	1 mb	>0.9	5 mb
Humidity	Solid state	%	0 to 100%	1% RH	>0.9	5% RH
Noise <sup>#6</sup>	Omnidirectional mic	dB	35 to 100 dB SPL	20 Hz – 20 kHz	>0.8	1 dB

## WIND SPEED & DIRECTION SENSOR

Sensor	Type	Units	Range	Resolution	Accuracy <sup>#7</sup>
Wind speed	Solid state	m/s	0 to 30 m/s	0.01 m/s	2%
Wind direction	Solid state	° degrees	0 to 359 °	1 °	2 °

## SENSOR LIFE

Sensor Type	Expected lifespan	Notes
Electrochemical	2 years <sup>#8</sup>	See AQMesh standard operating procedure
NDIR	5 years	See AQMesh standard operating procedure
Solid state	5 years	See AQMesh standard operating procedure
Omnidirectional microphone	5 years	See AQMesh standard operating procedure
Optical particle counter	2 years <sup>#8</sup>	Maintenance dependent on application & settings <sup>#9</sup>

## POWER

Option	Expected lifespan	Notes
External DC	>5 years	9 – 24V DC
Lithium metal battery pack <sup>#10</sup>	9-15 months 1 month	Estimate, gas only Estimate, with particulates
External high capacity battery pack <sup>#10</sup>	22-38 months 2-4 months	Estimate, gas only Estimate, with particulates
NiMH rechargeable battery pack	1 month	Estimate, gas only Not recommended for particulates
Solar power pack	>5 years	Change internal lead-acid battery every 24 months

## PHYSICAL

<b>Enclosure</b>	ABS, protection IP65
<b>Environmental</b>	Temperature range: -20°C to +40°C Humidity range: 15 to 95% RH
<b>Mounting</b>	Pod supplied with mounting bracket for walls and bracket / clips for posts 52mm-152mm diameter
<b>Approx. size &amp; weight</b>	Length: 170mm (pod only), 200mm (including the mounting bracket) Width: 225mm Height (excluding antenna): 240mm Height (including antenna): 360mm Weight: 2 – 2.7kg

## DATA ACCESS & COMMUNICATIONS

<b>Communication</b>	Raw data sent to server by cellular network. Worldwide coverage 4G/5G LTE Cat M1/NB1 with 2G fallback, within the following bands:- B1 (2100), B2 (1900), B3 (1800), B4 (AWS 1700), B5 (850), B8 (900), B12 (700), B13 (700), B18 (800), B19 (800), B20 (800), B26 (850), B28 (700)  Optionally- on request only- worldwide coverage:- 2G (B2, B3, B5, B8) 3G (B1, B2, B4, B5, B6, B8, B19) 4G (B1, B2, B3, B4, B5, B7, B8, B8_US, B9, B12, B13, B14, B18, B19, B20, B25, B26, B28).
<b>Measurement period</b>	Variable, from 1 minute to 1 hour
<b>Transmission frequency</b>	Variable, from 5 minutes to 12 hour intervals
<b>Server software</b>	Web browser based Processing of sensor output to give reading

Product designs and specifications are subject to change without prior notice.

The user is responsible for determining the suitability of the product.

\*h denotes when used with optional heated inlet for PM monitoring

#1 From sensor manufacturer's specification. This data was derived from independent lab tests. Standard test conditions are 20°C and 80% RH and in the absence of interfering gases. Tested range is -30°C to +30°C.

#2 Readings provided below this level, however due to interferences the level of uncertainty is greater than at higher levels of the target pollutant.

#3 Typical correlation co-efficient derived from extensive global co-location comparison testing against certified reference.

#4 Best "out of the box" accuracy without any local scaling/calibration against reference.

#5 Mass estimation based on standardisation of particle shape and density. Range is based on optical range of 0.3-30µm particle size.

#6 Noise measures average noise and peak noise. Peak noise is the highest recorded value over the gas reporting interval while average noise is calculated using all noise samples over the same period.

#7 Wind speed and direction stated accuracy is at 12m/s

#8 Electrochemical sensors and particle sensors carry a 12-month warranty.

#9 Detail of maintenance required is listed in the standard operating procedure.

#10 Subject to carrier restrictions on dangerous goods.

#11 Values are based on testing for Ethylene Oxide (EO) and correction factors will affect these results

We are supporting you to deliver  
a world class service, every day,  
in every sector...

## LOCATIONS

### LONDON, HEATHROW

#### Sunbelt Rentals UK Test & Monitoring

242-252 London Road, Staines, London TW18 4JQ

0333 122 3126

[www.sunbeltrentals.co.uk/find-a-depot/london-heathrow](http://www.sunbeltrentals.co.uk/find-a-depot/london-heathrow)

### REDCAR

#### Sunbelt Rentals UK Test & Monitoring

Unit 5 Kirkleatham Business Park, Redcar TS10 5SQ

0370 330 6021

[www.sunbeltrentals.co.uk/find-a-depot/teesside](http://www.sunbeltrentals.co.uk/find-a-depot/teesside)

### STOKESLEY

#### Sunbelt Rentals UK Test & Monitoring

2 Ellerbeck Way, Stokesley Business Park, Stokesley, North Yorkshire TS9 5JZ

01642 718 900

[www.sunbeltrentals.co.uk/find-a-depot/stokesley](http://www.sunbeltrentals.co.uk/find-a-depot/stokesley)



[www.inlec.com](http://www.inlec.com)

Order Online with Next Day  
Delivery, Online Chat & Online  
Account Management



★ Trustpilot

View our trustpilot score



STOKESLEY  REDCAR

 HEATHROW

0370 330 6021

[instrumentation@sunbeltrentals.co.uk](mailto:instrumentation@sunbeltrentals.co.uk)

[testequipment@sunbeltrentals.co.uk](mailto:testequipment@sunbeltrentals.co.uk)

[www.sunbeltrentals.co.uk](http://www.sunbeltrentals.co.uk)

